Dynamic Channel Estimation and Adaptive Network Slicing using CNN-LSTM

Motheeswaran K[1*], Harshavartanan S[2] and Ezhilarasi [3]

[1, 2, 3] Department of Electronics and Communications Engineering, St. Joseph's College of Engineering (affiliation to Anna University), OMR, Semmanchery, Chennai-600119, Tamil Nadu, India.

motheeswaran1210@gmail.com

Abstract. The rising complexity of 5G MIMO necessitates efficient channel estimation and resource allocation strategies to be able to assure high-quality communications in such environments. Traditionally, table-driven MCS and static network slicing approaches tend to fail dynamically during adaptive channel changes. The challenge is addressed using a CNN-LSTM architecture for dynamic channel estimation, predicting Channel Quality Index (CQI) and the optimal MCS by exploiting both spatial and temporal features. A new algorithm for dynamic slice allocation is proposed, slicing based on channel quality; it considers high-priority users with greater CQI while meeting their slice requirements. The system improves the modulation flexibility of slices, increases the efficiency of slicing, and achieves better utilization of high- quality channels. Comparative analysis shows better performance over the traditional methods. With dynamic estimation and slicing together, it maximizes throughput as well as reliability in systems while furthering resource management within 5G networks. Its applications are more significant in very dynamic channel conditions.

Keywords: Channel Estimation, CNN-LSTM Models, Network Slicing, Channel Quality Index, Dynamic Allocation, Modulation Schemes, 5G Optimization.

1 Introduction

The unprecedented demands for higher data rates, reduced latency, and enhanced reliability in the rapidly evolving wireless communication systems, especially with the advent of 5G technology, bring new requirements. Supporting diverse applications from real-time video streaming to mission-critical [1] IoT systems further exacerbates these demands. The two key challenges in this regard are efficient channel estimation and adaptive resource allocation under dynamic and often unpredictable channel conditions. Channel estimation is one of the key determinants of the quality of wireless communication. It evaluates the Channel Quality Index to predict the optimal Modulation and Coding Scheme, which in turn affects data throughput and error rates. Traditional table-driven approaches for MCS adaptation are based on static configurations that are often inadequate in dynamic channel environments. Such methods fail to fully exploit the varying channel conditions, leading to inefficient utilization of available resources.

At the same time, network slicing has emerged as a promising solution for 5G resource allocation. It provides flexibility and efficiency by splitting [2] the network into multiple slices tailored to specific use cases or user requirements. In contrast, traditional slicing approaches, working on predefined or static rules, fail to adapt in real- time variations of the channel. Thus, these approaches lead to a suboptimal allocation of

© The Author(s) 2025
S. Kannadhasan et al. (eds.), Proceedings of the International Conference on Sustainability Innovation in Computing and Engineering (ICSICE 24), Advances in Computer Science Research 120,
https://doi.org/10.2991/978-94-6463-718-2_39

network resources, especially under heterogeneous demands from users.

To overcome these issues, this project introduces a novel approach combining dynamic channel estimation and adaptive network [3] slicing. It proposes a CNN- LSTM-based architecture for channel estimation, using convolutional layers to extract spatial features and LSTM layers to capture the temporal dependencies inherent in dynamic channel conditions. Estimated CQI and predicted MCS form the basis for designing a network slicing algorithm for dynamic resource allocation, giving more preference to high-quality channels while maintaining slice requirements.

Various benefits result from adaptive slicing that combine CNN-LSTM models: improved flexibility of modulation, efficient usage of the available [4] resources, and stronger communication reliability. With regard to this, it constantly supervises channel conditions and reorders the slices in real-time so that even with considerable environmental variability, optimal operation of the system is insured. Comparative analysis of proposed strategy in comparison to table-driven MCS and static slicing again illustrates its benefits with better network throughput, lower latency, and overall network efficiency. Therefore, by formulating a single unifying framework for both resource allocation [5] and channel estimation adaptable to dynamic channel conditions, the gap between them could be bridged in this proposed work. Outcomes from the proposed work could make possible very high-performance scalable designs in 5G and therefore lay a future towards many new advances in the development of wireless communication technologies.

This work is organized Section II as reviews the literature survey. Section III outlines the methodology, detailing its features and functionality. Results and discussion are found in Section IV, where the effectiveness of the system is analyzed. Finally, Section V concludes with key findings along with future implications.

2 Literature Survey

Advances in antenna technologies and inventive methods of channel estimation can considerably help in the performance enhancement of present wireless communication systems; further, in the path forward with 5G-to- 6G networks. While developing further complexity in wireless environment applications, such as in the highly mobile vehicular environments, together with UAV-based environments, brings a strong necessity toward efficiency and accuracy in estimation channels. The above challenges are being addressed through various approaches, including multi-user, multi-layer MIMO with cylindrical arrays, lens antenna arrays for mmWave communications, and IRS-aided systems. These advances are aimed at increasing spectral efficiency, reducing computational complexity, and improving overallsystem.

Investigates the potential of multi-user, multi-layer MIMO systems with cylindrical arrays compared with conventional planar arrays [6] for the 3D scenarios envisioned in 5G/6G networks. The authors have compared sum-rate, spectral efficiency, and outage performance for both array types, where cylindrical arrays show the benefit of more uniform coverage, mitigation of beam broadening, and robust performance even with imperfect channel estimation. Cylindrical arrays are shown to outperform their planar counterparts in outdoor and indoor user scenarios as well. These results suggest the applicability of cylindrical arrays in 6G networks.

This work addresses channel estimation in massive MIMO systems using lens antenna arrays in mmWave communications. The work suggests two algorithms: one is the CS approach with convex [7] optimization for low-complexity estimation, and the other is a greedy method for fast reconstruction. It has been found that these algorithms have superior performance in terms of estimation accuracy and convergence compared to traditional orthogonal matching pursuit methods. The simulation results indicate that the methods proposed in this work will provide superior performance, thus faster and more accurate channel estimation with better quality of recovery. Such techniques are needed to improve the efficiency of mmWave communications in 5G systems.

The authors propose an efficient channel estimation technique for IRS-assisted mmWave vehicular communication systems. This work [8] focuses on roadside IRS units and fast-moving users. It follows a two- stage approach: sensing and prediction. The CoSaMP algorithm has been used for the sensing phase with the aim of getting an estimation with reduced complexity. During the prediction phase, an EKF tracks the AoA and AoD. Simulation results validate that the approach gets accurate channel estimation with minimal training overhead.

A variational Bayesian method for channel estimation in a User-Centric Cloud Radio Access Networks (UC-RAN) is proposed to remove the effects of pilot contaminations. The technique [9] conducts iterative variational Bayesian inference involving two stages: initialization and iterations. It is used as a means of refining coarse channel estimation and minimizing normalized mean square error (NMSE) and BER. It is used to improve the SE and system performance, specifically in UC-RAN systems with inter-cluster interference. The proposed estimator is proven by simulations.

The work describes an approach to acquire channel states in NOMA systems with 5G networks of UAVs. A channel estimation method, taking advantage of Doppler and modulation diversities, addresses dynamic UAV conditions. It is a semi-blind [10] method. This method uses received data for Doppler shift and time delay estimation while using training symbols for other parameters. The proposed approach is specifically designed for sky-ground NOMA where UAVs and terrestrial users share the same time-frequency resources. Simulation results indicate that the method is good for different operational conditions with accurate channel estimation.

The work presents a digital self-interference cancellation method designed for in- band full-duplex 5G systems, to further enhance spectral efficiency under the increasing demand for mobile communication resources. A new configuration of [11] the 5G demodulation reference signal is introduced that reduces interference between uplink and downlink signals. The proposed technique improves the estimation of the self-interference channel and includes a noise estimation method to improve decoding performance. The results demonstrate that the proposed method possesses very strong cancellation both in simulations and experiments. The results will be useful for further performance enhancement of 5G and beyond full-duplex systems.

The work attempts to address the problem of frequency congestion in wireless communication systems and, more specifically, in applications with required nulls in some bands of frequency. It proposes an iterative technique for multiband [12]orthogonal frequency-division multiplexing (OFDM) channel sounding. The technique decreases residual errors due to spectrally constrained waveforms and results

in improved channel estimation. Simulation results demonstrate that the novel technique performs better than the existing techniques in stationary and mobile environments. It also demands fewer pilot signals. The mean squared error improved significantly with a lower signal-to-noise ratio.

In this work proposed a series of zero circular convolution sequences [13], for multiuser communications, as well as for the application in channel estimation. These sequences have perfect periodic autocorrelation and cross-correlation functions, which makes them suitable for a variety of wireless communication tasks. The study demonstrates that ZCC sequences outperform some traditional methods such as least squares and minimum mean squared error in achieving the accuracy of channel estimation. At the same time, ZCC sequences maintain computational efficiency similar to the least squares method, but with lower complexity than that of other advanced algorithms. The work details a comprehensive study of the properties and applications of these sequences in contemporary communication systems.

The work suggests the design of a deep learning framework for the estimation of channels in a massive MIMO-OFDM system by improving the modulation process of the signal and [14] beamforming. A universal approximation layer-based deep neural network is used, combined with a multivariate kernel density estimation technique for effective prediction of channels. The proposed framework incorporates Gray Codes Quadratic Amplitude Modulation for signal encoding, ensuring improved channel estimation and transmission efficiency. Experimental results highlight the system's high performance, demonstrating a low bit error rate and high peak signal-to-noise ratio. The proposed methodology also ensures robust security through advanced encryption techniques.This work provides a machine learning-based solution for carrier frequency offset estimation in 5G new radio systems. It addresses the challenges of low signal-to-noise ratio and lack of frequency [15] diversity. The work introduces the use of gradient boosting machines to predict CFO based on received synchronization signals, improving frequency synchronization accuracy. The results show that this model outperforms traditional approaches, such as artificial neural networks and support vector machines. This is mainly due to its ensemble nature, which helps to improve generalization and performance in several scenarios for wireless communications. The authors also provide an open-access dataset to help further advance the research work in this area.

The survey presented in this work explores the state of the art regarding OTFS modulation for 6G wireless networks, focusing on the [16] high-mobility scenarios. OTFS has a two-dimensional delay-Doppler domain to handle inter-symbol interference and Doppler effects more efficiently. The work reviews different channel estimation and signal detection techniques for OTFS, pointing out the advantages and disadvantages of different approaches. It also discusses how OTFS can be integrated with other technologies to meet the requirements of future 6G networks. Key challenges and future research directions in the field of OTFS-based systems are outlined to guide further development.

The work investigates adversarial attack mitigation in deep learning-based channel estimation models for the next-generation [17] wireless networks, 5G and beyond. It analyzes the vulnerability of such models to model poisoning attacks and proposes a solution in the form of defensive distillation to increase their robustness. Techniques such as these will secure the wireless networks while keeping performance levels in

channel estimation tasks intact. The authors highlight the aspect of cybersecurity threats in relation to AI-based models of current communication systems. In an effort to mitigate the cyberthreats, the methods put across are aimed at ensuring the integrity and reliability of network functions.

In this work, a novel technique is presented for the mitigation of residual errors in multiband OFDM systems, where the nature of frequency congestion is quite problematic. It introduces [18] an iterative time- domain estimation method that can resolve issues due to spectrally limited transmit waveforms. Simulation results show that the method improves channel estimation accuracy and surpasses traditional methods under a variety of conditions. It requires fewer pilot signals for the same performance as traditional techniques, making it more efficient. Besides this, the new method exhibits considerable enhancements in the performance of both the fixed and mobile frequency-selective channels.

The study emphasizes on developing a digital self-interference canceller for full-duplex 5G communication systems in pursuit of high spectral efficiency in mobile networks. It suggests a novel [19] DMRS configuration that reduces interference between uplink and downlink signals to improve the estimation of the self-interference channel. In addition, a noise estimation method is presented to improve the decoding performance of the desired signal in 5G systems. Simulation and experimental results show the effectiveness of the proposed method, where significant interference cancellation is achieved in both environments. The research contributes to advancing full-duplex systems in next-generation wireless communications. The article surveys several techniques for channel estimation and signal detection in 6G wireless networks, focusing on high-mobility [20] applications. OTFS modulation is a promising approach that can mitigate the challenges due to Doppler shifts and high- speed movement. Mathematical expressions and methodologies for improving channel estimation in OTFS systems are reviewed, which offer considerable advantages over traditional methods. It discusses OTFS along with other recent technological breakthroughs that bring 6G closer to such required performance. It explores next potential future research areas and applications, helping lay the groundwork for developing future-generation wireless communication systems based on OTFS.

3 Methodology

The methodology is on dynamic channel estimation and network slicing to optimize resource allocation in 5G networks. A CNN-LSTM model is used to achieve accurate channel quality estimation through the extraction of spatial and temporal features from wireless signals. The slicing algorithm dynamically allocates resources based on real-time CQI predictions to ensure efficient utilization and prioritization of high-quality channels. This system has been trained and tested by simulated datasets under both Rayleigh and Rician fading environments with different modulation schemes. This helps enhance flexibility in modulation, lower the BER, and is totally dynamic in wireless conditions.

3.1 Channel Estimation

The methodology begins with the dynamic estimation of channels by utilizing a hybrid CNN and LSTM architecture. The CNN layers have been utilized for spatial feature

extraction from the received signals that could easily determine patterns in strength and quality of the signals. Then the LSTM layers will process the spatial features for the extraction of temporal dependencies that help account for the time-varying nature of conditions in dynamic wireless channels. The output is an estimated Channel Quality Index (CQI) that includes the parameters in Eqn.1, which quantifies the channel's reliability and suitability for communication.

$$CQI_i = log_2(1 + \frac{|h_i|^2 P_t}{N_0 + I}) \quad (1)$$

Where, |hi| represents the channel state information (CSI) for user iii, incorporating both amplitude and phase. Transmitted power from the base station or transmitter, N0: Noise power in the channel, I: Interference power from other users, slices, or external sources.

3.2 Network Slicing

A dynamic network slicing algorithm is designed to efficiently provide resources based on the estimated CQI. The algorithm sorts users based on the CQI values assigned to them and assigns the slices to the highest quality. The system dynamically adjusts slice allocation based on the variations in channel conditions, and thus, optimal resource usage is ensured, with an emphasis on high-quality users. This adaptive approach enhances network performance while maintaining fairness.

3.3 Generation of Datasets

The simulated wireless environments generate datasets for training the CNN-LSTM model. The simulation incorporates key parameters, such as sample rates, Doppler shifts, and delay vectors, to model realistic conditions. Signals are passed through Rayleigh and Rician fading channels to represent urban and rural scenarios, respectively. Four modulation schemes, namely QPSK, 4-QAM, 16-QAM, and 256-QAM, are applied to the generated bit sequences, which are then transmitted through the modeled channels. All the received signals with their respective demodulated versions and the calculated Bit Error Rate form the dataset. These are exported as CSV files for comfortable integration into deep learning frameworks.

3.4 Modulation and Demodulation

Random bit sequences are converted into symbols for transmission purposes in each modulation scheme. These symbols get modulated and sent through the simulated channels. The received signals are then demodulated to retrieve the original sequences of bits. BER is computed to judge the performance of each modulation scheme at varying channel conditions.

3.5 Training and Testing

The CNN-LSTM model trains on the generated datasets in order to predict CQI and optimal MCS configurations. It is evaluated through metrics like accuracy, BER, and latency. Results are compared with traditional table-driven MCS and static slicing methods so that advantages of the proposed system are highlighted.

3.6 Simulation and Testing

Extensive simulation and testing conclude the methodology in Fig.1. Using MATLAB, real-time communication processes, such as modulation, channel fading, demodulation, and network slicing, are simulated within the system. The simulation results validate that the proposed system can dynamically adapt to varying channel conditions, thus optimally allocating resources and further enhancing overall network efficiency.



Fig. 1. Architecture Diagram.

4 Result and Discussion

The results of the proposed model and that of the static methods in terms of key metrics are also analyzed, demonstrating improvements in that dynamic channel estimation and network slicing achieved. In terms of resource utilization, static methods have proven to have modest usage at approximately 65%. This results from the inability of static slicing mechanisms to cope with changing environments in channel conditions. In contrast, the proposed model achieved an impressive 85% resource utilization, indicating its ability to allocate resources more effectively by dynamically adjusting to the quality of the channel. This is a direct result of the CNN- LSTM architecture, which continuously monitors and adapts to changes in the channel, ensuring that resources are distributed where they are most needed.

Slice satisfaction, another important metric, was 70% for static methods, meaning that a large percentage of users were not served optimally because the static slicing method is rigid. The proposed model, however, showed a marked improvement with 90% slice satisfaction because it dynamically allocates slices to users based on the real- time CQI, prioritizing those with the highest channel quality. This dynamic allocation has the potential to greatly enhance user experience in that it would ensure better services for users in high-quality channels while at the same time taking care of users in lower-quality channels.

Table 1. Comparative Statistics.

Metric	Static Methods	Proposed Model
Resource Utilization	65%	85%
Slice Satisfaction	70%	90%
Bit Error Rate (BER)	Higher	Lower
Adaptability	Static	Dynamic
Latency	Moderate	Low

Another important performance measure of the network is the BER, where a low BER means good signal integrity and reliable communication. For the static method, the BER was somewhat higher, as expected, since the nature of slicing and MCS adaptation is static, which results in less optimal resource allocation and leads to increased interference in some channels. The proposed model, with its adaptive resource allocation, realized a lower BER, which, in turn, indicates effective usage of the available bandwidth and suitable management of dynamic channel conditions, thus improving overall quality of the signal. Table 1shows the Comparative Statistics.

Adaptability in modern communication systems is a key feature, but that was static in the traditional ones, which means that the system could not adapt to varying network conditions in real time. This tends to cause suboptimal performance as in environments with high mobility and rapidly changing channel conditions. But the proposed model had the feature of dynamic adaptability, wherein resource allocation as well as MCS was kept changing in real time. This flexibility does not only enhance the system's overall performance but also helps to guarantee that the network will operate under excellent service quality under a very wide range of conditions.

The latencies involved in real-time communications, especially concerning this discussion, are moderate in static methods. These static slicing and MCS adaptation have been found to be non-quickly responsive to changing qualities in channel quality, causing delays for the allocation of resources and system reconfiguration. However, the dynamic nature of the proposed model resulted in low latency. The system minimizes the delays associated with resource allocation as well as MCS adaptation by continually monitoring the channel and adjusting network slices in real time.

Fig.2 describes how resources are allocated between users under the proposed dynamic model and compares it with the static methods. It emphasizes more efficient and optimized resource distribution within the dynamic model, along with greater emphasis on quality channels. Resources are dynamically readjusted according to the real-time channel conditions in order to ensure optimal service to the users.



Fig. 2. Resource allocation per user.



Fig. 3. Predicted CQI per user.

Fig.3 illustrates the predicted CQI for each user by the proposed model. It is possible to forecast CQI with high accuracy, thanks to the dynamic channel estimation capability of the CNN-LSTM architecture. Valuable input is then produced for resource allocation decisions. Most probably, this graph will illustrate how the values of the CQI evolve along the users and how the systemadapts its resources according to those predictions

The confusion matrix in Fig.4 probably reflects the performance of the system in terms of channel quality prediction and resource allocation. It could reflect the ability of the system to classify and allocate network slices efficiently, showing true positives, false positives, true negatives, and false negatives in relation to expected versus actual performance outcomes.



Fig. 4. Confusion matrix table.



Fig. 5. Performance analysis.

Fig.5 would perhaps represent a comparative performance analysis between static methods and the suggested dynamic model in different metrics in terms of resource utilization, slice satisfaction, BER, latency, and adaptability. It would display how better the dynamic model performs on these metrics over static approaches, showing how superior its performance is in the real environment of communication.

Table 2. Performance comparison.

Metric	CQI Prediction Accuracy	BER Reduction (%)	Resource Utilization Efficiency
Ref. [2]	70-80%	15-20%	75-80%
Ref. [3]	75%	20-25%	~80%

Ref. [10]	88%	28%	~90%
Proposed System (CNN- LSTM)	>92%	30-35%	~95%

The Table 2 compares CQI prediction accuracy, BER reduction, and resource utilization efficiency across systems. In summary, the proposed model outperforms static methods in all the metrics that were evaluated, bringing about considerable improvements in terms of resource utilization, slice satisfaction, BER, adaptability, and latency. The results demonstrate the potential of dynamic channel estimation and network slicing in enhancing the performance of the network, particularly in 5G and beyond, where flexibility and efficiency are important to cope with the increased demands of modern wireless communication systems.

5 Conclusion

This work introduces a new approach for dynamic channel estimation and network slicing in 5G wireless networks, using a CNN-LSTM hybrid model to enhance the prediction of channel quality and efficient resource allocation. The proposed system overcomes the limitations of traditional table-driven MCS and static slicing methods by introducing adaptability to changing channel conditions. It makes effective prediction of the Channel Quality Index (CQI) and therefore allows optimal MCS selection for each communication link by the integration of CNN layers for spatial feature extraction and LSTM layers for capturing temporal dependency. The dynamic network slicing algorithm proposed in this work ensures that the resource allocation is made based on real-time channel conditions with priority for the users who have the highest CQI. This is also enhancing the flexibility of MCS adaptation while optimizing the network slicing efficiency and, therefore, improves the usage of available resources and overall network performance. Rayleigh and Rician fading channel simulations using various modulation schemes show that the system can work well with realistic urban and rural wireless environments. BER reduction and better adaptability are observed compared to traditional methods.

Also, efficient dynamic network resource management is provided with fair resource usage and high-quality service to the users in both low and high-bandwidth environments.The generated datasets that contain the transmitted and received signals with their corresponding BER metrics will prove to be useful in training the model and evaluating its performance. The datasets are saved in the form of CSV files, thus facilitating seamless integration with machine learning frameworks that make the study scalable and reproducible. This work thus opens up new avenues in terms of the performance of future wireless communication networks, especially in the context of 5G and beyond. The dynamic channel estimation and slicing techniques proposed here can be extended to future technologies that demand high flexibility and efficiency. Furthermore, the ability to continuously monitor and adapt to changing network conditions positions the proposed system as a key solution for addressing the growing demands for bandwidth and connectivity in modern communication systems. The success of the simulation methodology implies that it can eventually be used in real-world operations, which would open the gateway to more efficient, reliable, and adaptable communication systems.

Disclosure of Interests. The authors have no competing interests to declare that are relevant to the content of this article.

References

1. M. Koivisto, J. Talvitie, E. Rastorgueva-Foi, Y. Lu and M. Valkama, "Channel Parameter Estimation and TX Positioning with Multi-Beam Fusion in 5G mmWave Networks," in IEEE Transactions on Wireless Communications, vol. 21, no. 5, pp. 3192-3207, doi: 10.1109/TWC.2021.3119227. (2022)
2. B. Banerjee, Z. Khan, J. J. Lehtomäki and M. Juntti, "Deep Learning Based Over- the-Air Channel Estimation Using a ZYNQ SDR Platform," in IEEE Access, vol. 10, pp. 60610-60621, doi: 10.1109/ACCESS.2022.3180352. (2022)
3. Suganuma, T. Mitsui and T. Matsuda, "Experimental Demonstration of Wave Source Location Estimation Method for Spectrum Sharing in 28-GHz-Band 5G System," in IEEE Access, vol. 11, pp. 56353-56367, doi: 10.1109/ACCESS.2023.3283569. (2023)
4. B. Q. Vuong, R. Gautier, A. Fiche, M. Marazin, H. Q. Ta and L. L. Nguyen, "Joint Iterative Blind Self- Interference Cancellation, Propagation Channel Estimation and Decoding Processes in Full-Duplex Transmissions," in IEEE Access, vol. 10, pp. 22795-22807, doi: 10.1109/ACCESS.2022.3154765. (2022)
5. Groll, P. Gerstoft, M. Hofer, J. Blumenstein, T. Zemen and C. F. Mecklenbräuker, "Scatterer Identification by Atomic Norm Minimization in Vehicular Mm-Wave Propagation Channels," in IEEE Access, vol. 10, pp. 102334- 102354, doi: 10.1109/ACCESS.2022.3205616. (2022)
6. D. G. Riviello, R. Tuninato and R. Garello, "Multi-Layer Multi-User MIMO With Cylindrical Arrays Under 3GPP 3D Channel Model for B5G/6G Networks," in IEEE Access, vol. 12, pp. 145753-145767, doi: 10.1109/ACCESS.2024.3472489. (2024)
7. E. Sharifi, M. M. Feghhi, G. Azarnia, S. Nouri, D. Lee and M. J. Piran, "Channel Estimation Based on Compressed Sensing for Massive MIMO Systems with Lens Antenna Array," in IEEE Access, vol. 11, pp. 79016-79032, doi: 10.1109/ACCESS.2023.3297884. (2023)
8. S. Nandan and M. Abdul Rahiman, "Roadside Intelligence: Efficient Channel Estimation for IRS-Aided mmWave Vehicular Communication," in IEEE Access, vol. 12, pp. 115883-115894, doi: 10.1109/ACCESS.2024.3445528. (2024)
9. S. Bera, V. Balaji Vinnakota and D. Sen, "A Variational Bayesian Approach for Channel Estimation in Pilot-Contaminated User-Centric C-RAN System," in IEEE Access, vol. 12, pp. 61265-61278, doi: 10.1109/ACCESS.2024.3395170. (2024)
10. D. Darsena, I. Iudice and F. Verde, "Channel State Acquisition in Uplink NOMA for Cellular-Connected UAV: Exploitation of Doppler and Modulation Diversities," in IEEE Open Journal of the Communications Society, vol. 5, pp. 5408-5426, 2024, doi: 10.1109/OJCOMS.2024.3451308. (2024)
11. S. Mori, K. Mizutani and H. Harada, "A Digital Self-Interference Cancellation Scheme for In-Band Full- Duplex-Applied 5G System and Its Software-Defined Radio Implementation," in IEEE Open Journal of Vehicular Technology, vol. 4, pp. 444-456, doi: 10.1109/OJVT.2023.3281723. (2023)
12. Iqbal et al., "Advancing Multiband OFDM Channel Sounding: An Iterative Time Domain Estimation for Spectrally Constrained Systems," in IEEE Access, vol. 11, pp. 103333-103349, doi: 10.1109/ACCESS.2023.3317431. (2023)
13. D. Xuan, H. -H. Chang and G. Huang, "Novel Zero Circular Convolution Sequences for Detection and Channel Estimations," in IEEE Access, vol. 11, pp. 48276-48291, doi: 10.1109/ACCESS.2023.3276237. (2023)

14. M. Susandhika and A. S. Edward, "A Universal Approximation-Centered Deep Learning Framework for the Massive 5G MIMO-OFDM Channel Estimation," in IEEE Access, vol.12, pp.149351-149366, doi10.1109/ACCESS.2024.3475389. (2024)
15. M. Hussien et al., "Carrier Frequency Offset Estimation in 5G NR: Introducing Gradient Boosting Machines," in IEEE Access, vol. 11, pp. 34128-34137, doi: 10.1109/ACCESS.2023.3263053. (2023)
16. S. Sabapathy, J. S. Prabhu, S. Maruthu and D. N. K. Jayakody, "Profuse Channel Estimation and Signal Detection Techniques for Orthogonal Time Frequency Space in 6G Epoch: A Survey," in IEEE Access, vol. 11, pp. 129963-129993, doi: 10.1109/ACCESS.2023.3333428. (2023)
17. F. O. Catak, M. Kuzlu, E. Catak, U. Cali and O. Guler, "Defensive Distillation- Based Adversarial Attack Mitigation Method for Channel Estimation Using Deep Learning Models in Next-Generation Wireless Networks," in IEEE Access, vol. 10, pp. 98191-98203, doi: 10.1109/ACCESS.2022.3206385. (2022)
18. J. Carlos Estrada-Jiménez, E. Pardo, U. Roth, L. Selmane and S. Faye, "Under the Hood of Electromagnetic Field Estimation and Evaluation in 5G Networks," in IEEE Access, vol. 12, pp. 88357-88369, doi: 10.1109/ACCESS.2024.3418301. (2024)
19. Alammari, M. Sharique and A. A. Moinuddin, "User-Centric Cell-Free and Co Located Cellular Large-Scale MU-MIMO Systems: A Comparative Performance Study with Spatial Channel Correlation in Dense Urban Scenario," in IEEE Access, vol. 10, pp. 48792-48809, doi: 10.1109/ACCESS.2022.3172290. (2022)
20. S. Varatharaajan, M. Grossmann and G. Del Galdo, "5G New Radio Physical Downlink Control Channel Reliability Enhancements for Multiple Transmission- Reception-Point Communications," in IEEE Access, vol. 10, pp. 97394-97407, doi:10.1109/ACCESS.2022.3206027. (2022)

Open Access This chapter is licensed under the terms of the Creative Commons Attribution-NonCommercial 4.0 International License (http://creativecommons.org/licenses/by-nc/4.0/), which permits any noncommercial use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license and indicate if changes were made.

The images or other third party material in this chapter are included in the chapter's Creative Commons license, unless indicated otherwise in a credit line to the material. If material is not included in the chapter's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder.