Implementing an Arduino-Based System to Prevent Collisions and Detect Cracks on Rail Tracks

Kiran P S V R[1] and Veluru Pavan[2]

[1, 2] Department of Electronics and Communication Engineering, Saveetha Engineering College, Chennai, Tamil Nadu, India.

kiranpinisetti02@gmail.com

Abstract. In today's infrastructure, railway transportation systems are essential because safety is key to preventing mishaps and system failures. This work aims to outline the design and implementation of an Arduino-based system intended to detect cracks in railroad tracks and prevent collisions. A number of sen-sors are included in the proposed system, including piezoelectric or vibration sensors to detect cracks and ultrasonic sensors to prevent collisions. When possible, threats are detected, an Arduino microcontroller uses real-time data from multiple sensors to initiate emergency procedures and sound warnings. Vital data is sent to a centralized monitoring station via an advanced wireless connection module for quick analysis and action. Particularly designed to be financially feasible, energy-efficient, and easily expandable, the system is ideal for extensive deployment across railway networks. In order to improve the overall safety and dependability of railway operations, experimental and computa- tional results validate the system's accuracy in detecting fractures and preventing collisions. The initiative represents a significant step forward toward train transportation systems that are more intelligent, secure, and efficient.

keywords: Arduino infrastructure, Railway safety, Col- lision avoidance, Crack identification, Ultrasonic sensors, Vi- bration sensors, Wireless connection, Internet of Things in transportation.

1 Introduction

Given that railways play a vital role in enabling the move- ment of people and products across extensive networks, their efficacy and safety are of the highest importance. Railway tracks present significant risks to operating safety because they are subjected to a variety of environmental conditions and pressures that can lead to structural deterioration. The breadth of coverage, frequency of inspections, and real-time response capabilities are some of the limitations of traditional inspec- tion methods, such as manual inspections and fixed sensors. New solutions to these issues have been made possible by advanced advancements in wireless communication and sensor technology. Rail track monitoring can be greatly enhanced by Wireless Sensor Networks (WSNs), which offer the ability to collect data continuously and remotely. Including these technologies in in essence, the current rail infrastructure can lead to safer and more reliable rail operations by significantly improving the accuracy and timeliness of track inspections.

© The Author(s) 2025
S. Kannadhasan et al. (eds.), Proceedings of the International Conference on Sustainability Innovation in Computing and Engineering (ICSICE 24), Advances in Computer Science Research 120,
https://doi.org/10.2991/978-94-6463-718-2_95

Railway track angular deviations are detected using micro- electromechanical systems (MEMS) sensors, which are well- known for their small size and high sensitivity. These differ- ences could indicate potential fractures or track misalignment. To ensure timely feedback on the track's condition, the device is specifically designed to continuously monitor these angular fluctuations.

The system's integrated GSM module is activated by the MEMS sensors when they detect a significant change, sending an alert to a designated mobile number. This alert provides the exact location of the identified issue by utilizing GPS (Global Positioning System) technology. The system reduces the chance of accidents and improves track safety by enabling prompt intervention and maintenance through the transmission of real-time data.This strategy has many advantages. The first benefit is that it eliminates the need for tedious and inconvenient manual inspections. Second, it provides ongoing observation system capable of quickly identifying potential issues and fixing them before they get worse. Additionally, in- stantaneous data transmission ensures that maintenance teams can effectively and quickly address emerging problems, po- tentially preventing costly repairs and significantly enhancing the overall safety of the railway system.

The design and implementation of the proposed system will be covered in more detail in the sections that follow. This will include integrating GPS, GSM, and MEMS sensors with the Arduino platform. In addition, we will examine the system's effectiveness, potential applications, and implications for up- coming train track maintenance and inspection procedures.

2 Related Works

Rail track safety and inspection have advanced significantly, moving from traditional manual inspection methods to so- phisticated, technology-based solutions. At the forefront of these developments has been the integration of various sensor technologies, which has increased track monitoring's efficacy and accuracy. For example, [1] demonstrated a rail inspection system that incorporates gyroscopes and accelerometers into a wireless sensor network (WSN). The current system is able to track angular deviations and vibrations in real time, providing

Fig. 1. Shows Three Railway Officials Arrested Over Train Crash

valuable information for the prompt detection of potential issues. In order to improve the accuracy and speed of rail track data monitoring, this methodology highlights the growing reliance on sensor networks. In order to predict rail faults, later developments have combined machine learning algorithms with piezoelectric sensors. Piezoelectric sensors' ability to measure stress and strain in rail tracks was demonstrated by the authors of reference [2]. Machine learning algorithms were then used to analyze these readings and forecast potential malfunctions. By proactively identifying issues before they become critical, the application of this predictive methodology enhances maintenance plans, preventing accidents and mini- mizing disruptions. Fig. 1. Shows Three Railway Officials Arrested Over Train Crash.

GSM and GPS technology has been integrated into train track monitoring equipment to improve performance. In conjunction with GPS [3], a GSM-based communication system was proposed that addresses the transmission of real time location data through GSM and notifying maintenance personnel of detected track irregularities. Using this approach, maintenance personnel receive detailed information on the specific locations of imperfections, and can respond more quickly and effectively. [4] proposes integration of MEMS sensors with GSM communication, the feature of GSM makes it possible to provide monitoring of the train track in a better way. Besides track anomaly detection, this technology enhances the system's reliability and efficacy by transmitting data in real time.

Recent developments in tracking continous media streams prompted by integration of sensing technologies used in au- tonomous inspection vehicles have drastically changed the way of railway track monitoring. [5] has created a vehicle that can autonomously inspect and categorize rail faults thanks to the combined power of lidar and high-definition cameras. The vehicle can cover more ground this way, and inspection results are transmitted to a central system, enhancing the scope and accuracy of inspections. The application of automated inspections over large areas minimizes the need for manual inspections while increasing frequencies for monitoring.

Fiber optic sensors have also shown promise for monitoring railroad tracks. [6] employed fiber optic sensors to detect small defects on rails such as cracks and deformations. These sensors are capable of relay high-sensitivity, real-time monitoring information of the track condition. Additionally, [7] investigated hybridization of sensors, accelerometers and acoustic emission sensors, which support both invitations to detect defects on surface and interior defects, thus, increasing reliability of defect detection.

[8] describes the use of Internet of Things (IoT) technology to develop intelligent train monitoring systems. Integrating a network of Internet of Things (IoT) enabled sensors, the system is designed to continually monitor and evaluate track condition data, and support real time updates and proactive maintenance alerts. This smart strategy will not only enable advanced monitoring capabilities but also flexible maintenance measures.

Academics have also studied how effectively mobile inspection platforms drones, self-driving cars, etc. carry out inspections over long stretches of track. In a study by [9], the authors pointed out that these platforms provide a tremendous value in

terms of collecting significant amounts of data from the track's condition that centralize data analysis [9], thus guaranteeing overall inspections. In order to ensure a more accurate and robust estimation of track conditions, [10] also introduced a data fusion method that used data fusion of different sensors, for instance laser and ultrasonic sensors.

Innovations like these are representative of broad advances in rail track safety and inspection made possible by technology. The system proposed in this paper is inspired by this progress and it proposes a reliable, automated system for crack detection and collision avoidance by implementing MEMS sensors and GSM connectivity. In addition, by promoting the growth of rail infrastructure to meet the changing needs of society, this strategy aims to make rail systems safer and more dependable.

3 Methodology

The collision prevention system is an integration of MEMS sensors, Arduino microcontrollers, GSM connections, and GPS technology to detect crack on rail track. This enables the monitoring and alerts to be integrated into real time. The approach consists of 5 key elements: data processing, communication, sensor integration, and system design.

3.1 Design of the System

The technology is specifically engineered to surveil the state of rail tracks and identify any abnormalities that could indicate a risk, such as cracks or misaligned tracks. A microcontroller based on Arduino is a critical system component, serving as the primary processing unit for communication, data collection, and manipulation. It features a GPS module for tracking location, MEMS sensors for detecting vibrations and changes in angle, and a GSM module for sending alerts.

3.2 Selection of MEMS sensors

Sensitivity, compact size and less power consumption are the three areas of considerations while choosing MEMS sensors. To measure angular deviations and rail vibrations, Arduino platform integrates sensors such as accelerometers and gyroscopes. The accelerometer detects variations in acceleration across several axes, and the gyro- scope identifies rotational disturbances. Both inputs are needed to detect any inconsistencies or errors in the track.

On the other hand, the sensors are transversely positioned with fixed inter- vals on the train channel, to cover the train channel as a whole. Each individual sensor node is connected to an Arduino board, which gathers and analyzes the sensor data. The Arduino microcontroller aims to collect data from MEMS sensors at regular intervals, analyze the readings, and identify significant deviations from the expected standard values. Fig. 2. Shows the Obstacle Detection Flowchart



Fig. 2. Obstacle Detection Flowchart

3.3 Processing of Data

Statistical data processing is used to analyse sensor data in order to detect anomalies in the track. Algorithms are used on the Arduino microcontroller to read the raw sensor data and detect changes in the track condition. The algorithms decide if an abnormality is present by comparing the latest measured results with predetermined cutoff values. If the accelerometer reports a sudden spike in vibrations or if the gyroscope indicates an unexpected shift in angular position, the system looks for deviations above acceptable (normal) thresholds. It means that it considers the event to be something suspicious that should be investigated further once the given conditions are met.

3.4 Information Exchange and Notification

The system uses a GSM module interfaced with the Arduino to provide timely notification. The microcontroller activates the GSM module to send a notification when a possible deviation from the path is detected. The current message contains details about the detected issue and precise GPS recorded coordinates of the sensor node where the anomaly has been detected. GPS module will give accurate area system which assists maintenance man to Know exactly where the issue is and how to fix it.

Module GSM module is used for sending the SMS notifications to the specified mobile no. It allows maintenance workers to respond instantly and introduce preventive actions in real time. It is trained only when things go horribly wrong, and

is specifically designed to run autonomously with little human interaction (outside of routine maintenance and calibration of the detection devices).

3.5 System Testing and Calibration Evaluation

The system is subject to stringent testing and calibration procedures to guarantee accuracy and reliability. The system is tested on a mock railroad track where known anomalies are intentionally introduced to check that the sensor and the system can detect and report them. During calibration processes, the sensor readings and the threshold values are meticulously calibrated so that system closely reflects the specific track conditions. It is evaluated based on its ability to detect real-world track irregularities, the time taken to relay notifications and the accuracy of the latitude and longitude coordinates captured by GPS. Refinements that increase system dependability and efficiency are guided by test results.

3.6 Implementation and Incorporation

The technology is put into use on operational railroad tracks after validation. The current train safety regulations and monitoring systems are systematically integrated to ensure seamless operation. Giving maintenance teams instruction on how to operate the system and respond to emergencies ensures that the technology is used effectively in real-world scenarios.

3.6.1 Architecture Diagram Explanation

The Arduino Uno microcontroller, a widely used platform for embedded systems and prototyping, is the central com- ponent of this system. The entire setup, which consists of a number of sensors, actuators, and communication elements, creates an Internet of Things (IoT) system that can gather, process, and share data instantly. Source of electrical power by lowering the voltage to a suitable level for the Arduino and other external components, an external transformer controls the system. A power supply board then regulates the con- verted voltage, ensuring that all circuits including sensors, actuators, and communication modules—have a consistent and reliable supply of power. Measurement devices: The Arduino CPU processes the environmental data gathered by the system's multiple sensors. The purpose of the proximity sensor is to detect barriers or objects within a predetermined range. It is useful in a variety of applications, such as security systems, autonomous vehicles, and robot obstacle detection.

A device that produces ultrasonic waves and measures how long it takes for the waves to scatter back is called an ultrasonic sensor. Practical uses for the generated data include level detection in fluid containers, obstacle avoidance, and distance measurement. Because the infrared (IR) sensor is made to detect infrared light, it can be used for remote control, object detection, and proximity detection. The gadget can identify the presence of things and people that fall into a particular



Fig. 3. Shows Proposed Architecture

range. The Arduino can obtain real-time location data through the Global Positioning System (GPS) module, which makes it appropriate for use in location-based tracking, geofencing, and navigation systems. Fig. 3. Shows Proposed Architecture.

The Arduino uses pulse width modulation (PWM) to control the motor, allowing precise control of the motor's speed and direction. Numerous applications, including robotics, automa- tion, and motorized systems, benefit from this capability.

Buzzer: An early warning system or alert device is a buzzer. It can be set up to activate when certain events, like proximity detection, collision alerts, or system malfunctions, occur.

Liquid Crystal Display: The Visual Display Unit Present- ing current data like sensor measurements (e.g., proximity to the ultrasonic sensor, GPS coordinates, etc.), system condition, or alert notifications, the Liquid Crystal Display (LCD) serves as the system's visual interface. In applications that involve human interaction or surveillance, like industrial automation or security systems, precise visual feedback is crucial. Modules for Interaction

In order to facilitate data transfer with external systems as well as during system operation:The NodeMCU WiFi Module and the Arduino microcontroller can communicate se- rially thanks to the UART (Universal Asynchronous Receiver-Transmitter) module. The Arduino can send and receive data to and from the communication modules thanks to its role as an intermediary.

Communication with external networks or cloud-based In- ternet of Things (IoT) platforms is made easier by the NodeMCU WiFi Module, which adds wireless connectivity to the system. Data transmission from the sensors and system to an Internet of Things (IoT) webpage or guidance from remote interfaces enable remote monitoring, control, and data logging. The system can be used in a variety of IoT-

based applications, such as remote monitoring, smart homes, and industrial IoT, thanks to this feature.

Internet of Things Interface: Using NodeMCU WiFi Module this system can send the data to an IoT webpage and thus the user can monitor it remotely in real time from any part of the globe. By doing so the website can show sensor data, send an alert or let the user control the system remotely.

such as changing settings or switching the motor on and off. This ability not only enhances the scalability and usability of the system but also makes it appropriate to be adopted in IoT applications that require remote monitoring and control. 1. The System Electricity: The transformer and power supply board supply electricity to the system. Sensor Data Col- lection: Several proximities, ultrasonic, and infrared sensors as well as a GPS send environmental readings to the Arduino Uno every few milliseconds.

Algorithm: The Arduino evaluates the sensor data it gathered with predetermined logic and performs accordingly. For the buzzer system while detecting an object in a certain range it will sound. It can also use the PWM frequency to control the motor speed.

Communication and Control: By using the UART to connect to the NodeMCU WiFi module, the system sends data to an Internet of Things webpage that enables users to remotely monitor and control the system. For the purpose of local monitoring, the Arduino additionally displays real-time data on the LCD screen. Parts of an Arduino called actuators respond to commands from the Arduino while accounting for system logic and sensor inputs.

4 Result and Discussion

An Arduino Uno was used to integrate multiple sensors, actuators, and communication modules for the system shown in the block diagram to be successfully implemented and tested. The key conclusions drawn are presented in this paper: With the Arduino Uno, all sensors including proximity, ultrasonic, infrared, and GPS modules were successfully integrated.

Users were able to respond quickly because the sensors provided accurate real-time data that was clearly displayed on the LCD screen. control of motors using PWM,Using Pulse Width Modulation (PWM) signals generated by the Arduino motherboard, the motor ran. When the proximity or ultrasonic sensor detected an obstruction, for example, the system was able to successfully control the motor's speed and direction.

Alarm activation triggered by buzzer:

The connectivity of the Internet of Things (IoT) platform was efficiently enabled by the NodeMCU WiFi module. The transmission of real-time sensor data to an IoT portal enabled remote data and system health monitoring.The IoT interface would allow users to remotely control the system, allowing them to change sensor

settings and control the motor's power state.

Digital Liquid Crystal DisplayA user-friendly interface for local monitoring was provided by the LCD screen, which continuously displayed the most recent data gathered from the sensors. This was particularly helpful when a quick visual reaction was needed.

Internet of Things Website: The IoT website provided a comprehensive interface for remote monitoring. The system displayed sensor information such as GPS location, proximity, distance (as determined by ultrasonic emissions), and system status. The portal also demonstrates the system's ability to be used for remote automation applications by enabling users to control the motor and other actuators. The successful deployment of the system demonstrates the adaptability of an Internet of Things (IoT) focused control and monitoring platform driven by the Arduino Uno. Presented below are few pertinent topics for discussion:



Fig. 4. Show Output of Proposed System

Evaluation of Sensor Performance: During real-time data collection, the sensors GPS, proximity, ultrasonic, and in- frared all functioned dependably and consistently. The in- clusion of several sensors increased the system's utility by enabling a range of inputs. The proximity and ultrasonic sensors worked well in object detection situations, and the GPS module provided location tracking capabilities, so the system was suitable for tracking and mobile applications.In difficult situations, such as those with reflective surfaces, or when objects were far away, the accuracy of the ultrasonic sensor somewhat declined. When it came to detecting objects within a short range, it performed admirably. Fig. 4. Shows Output of Proposed System.

Pulse Width Modulation (PWM): PWM (permanent mag- net synchronous motor) control allowed for precise changes in direction and speed. In applications like robotics, automation, or smart car systems that demand a high degree of precision, accurate control is crucial.

Both the load and the power source, however, had a major impact on the motor's

performance. Using electric motors with higher power consumption or higher loads may require optimization.The Use of Buzzers as Warning Devices:

The buzzer was a very effective way to alert customers to a planned occurrence, like an object that was getting too close. Despite being simple, this audio input could be very important in security or safety applications.

More complex applications can be accommodated by using a variable-intensity or multi-tone buzzer to effectively convey complex alerts.

5 Conclusion

A number of sensors, actuators, and wireless communica- tion modules are skillfully combined in the Arduino Uno- based IoT-based system to provide real-time monitoring, con- trol, and data transfer. In handling multiple tasks, includ- ing collecting sensor data, regulating motors with PWM, and enabling remote communication through the NodeMCU WiFi module, the system showed resilience and compe- tence.Essential components like proximity, ultrasonic, infrared, and GPS sensors were incorporated to enable accurate en- vironmental detection, and the buzzer and PWM-controlled motor facilitated effective real-time responses and alerts. Im- mediate local monitoring was made possible by the addition of an LCD display, which enhanced usability. Furthermore, the IoT webpage made remote control and data visualiza- tion simple, demonstrating the system's suitability for IoT applications.Furthermore, the modular design of the system enables scalability, rendering it appropriate for a wide range of practical applications including smart homes, industrial automation, security systems, and smart vehicles. Neverthe- less, optimisation of the system for bigger deployments can be achieved via enhancements in power efficiency, network connection, and data security. Fig. 5. Shows Results.



Fig. 5. Shows Results

Disclosure of interest. The authors have no competing interests to declare that are relevant to the content of this article.

References

1. Aamir Shaikh and Siraj Pathan (2012) 'Research on Wireless Sensor Network Technology', in In- ternational Journal of Information and Education Technology Vol.2, No.5, pp. 476-479.
2. Arun,P and Saritha,S.andMartin,K.M. and Madhuku- mar,S.(2012) 'Simulation of zigbee based TACS for collision detection and avoidance for railway traffic',in International conference on advanced computing communication technolo- gies for performance application, paper ID 51.
3. Ajith Theja,K and Dr.Kumaresan,M. and Dr.SenthilKumar,K.(2015) Automated Unmanned Railway Level Crossing System Using WSN, International Journal of Innovative Research in Computer and Communication Engineering, Vol.3.
4. Bhavsar,S.S. andKulkarni,A.N(2016) 'Train collision avoidance system byusing RFID', In 2016 International Con- ference on Computing, Analytics and Security Trends (CAST), pp. 30-34. IEEE.
5. Cacciola,M. and Megali,G. and Pellicano, D.andCalcagno,S. and Versaci,M. and Morabito,F.C. (2012) 'Rotating Electromagnetic Field for Crack Detection in Railway Tracks', PIERS ONLINE, Vol. 6, NO. 3.
6. Chengbo, YU. and Yanfei, LIU. and Cheng, WANG. (2009) 'Research on ZigBee Wireless Sensors Network Based on ModBusProtoco-l', Published Online in Sci Res Vol.1, No. 1, pp. 43-47.
7. Christeena Joseph and Ayyappan,A.D. and Aswini,A.R. and Dhivya Bharathy,B.(2013) 'GPS/GSM
8. B Cacciola,M. and Megali,G. and Pellicano, D.and Calcagno,S. and Versaci,M. and Morabito,F.C. (2012) 'Ro- tating Electromagnetic Field for Crack Detection in Railway Tracks', PIERS ONLINE, Vol. 6, NO. 3.
9. Dhanabalu,T. and Sugumar,S. and Suryaprakash,S. and VijayAnand,A.(2015) "Sensor based identification system for Train Collision Avoidance", in IEEE Sponsored 2nd Interna- tional Conference on Innovations in Information Embedded and Communication Systems,p.no.1-2.
10. Dr. Riaz Ahamed, S.S. (2009) 'The Role of Zig- Bee Technology in Future Data Communication System', in Journal of Theoretical and Applied Information Technology Vol.5, Issue 2.
11. Parneet Dhillon and Dr. Harsh Sadawarti (2014) 'A Review Paper on Zigbee Standard', in International Journal of Engineering Research Technology Vol.3, Issue 4, ISSN (Online): 2278-0181.
12. Reddy,G.S and Ashok,B.(2016) 'Train Collision Avoid- ance System by using GSM Technology', International Journal of Advance Technology Innovative Research, ISSN: 2348- 2370, Vol 8, Issue21,pp.4005-4007.
13. Ramesh,S. (2011) 'Detection of Cracks and Rail- way Collision Avoidance System', International Journal of Electronic and Electrical Engineering, Volume 4, Number 3, pp.321-327.
14. P. Sittel, T. Scho¨nwa¨lder, M. Kumm, and P. Zipf, "ScaLP: A lightweighted (MI)LP library," in Proc. Methoden Beschreibungssprachen Modellierung Verifikation Schaltungen Systemen (MBMV), 2018, pp. 1–10.

Open Access This chapter is licensed under the terms of the Creative Commons Attribution-NonCommercial 4.0 International License (http://creativecommons.org/licenses/by-nc/4.0/), which permits any noncommercial use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license and indicate if changes were made.

The images or other third party material in this chapter are included in the chapter's Creative Commons license, unless indicated otherwise in a credit line to the material. If material is not included in the chapter's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder.