



The Relationship between Construction and Demolition Waste Minimisation and Sustainable Construction

Rohit Gade¹, Jeff Seadon² and Mani Poshdar³

¹ School of Future Environments, Auckland University of Technology, Auckland, New Zealand

² School of Future Environments, Auckland University of Technology, Auckland, New Zealand

³ School of Future Environments, Auckland University of Technology, Auckland, New Zealand

Abstract. Increasing urbanisation has become a global environmental concern, as half of the extracted natural resources are used for building construction. In addition, the factual claims made on socio-economic benefits achieved through Construction & Demolition (C&D) waste minimisation approaches are yet to be fully explored. Further, the majority's vested interest has neglected the life cycle approach for waste minimisation. Hence, this research provides a review of literature on C&D waste minimisation, considering cradle to cradle thinking to advocate Sustainable Construction. This research highlighted the state of the art of C&D waste minimisation approaches worldwide, including factors influencing waste generation, challenges in waste minimisation, and provides a conceptual waste minimisation framework. The framework identified key waste minimisation challenges over the project's life cycle. Some of the challenges are: poor building standards; lack of waste sorting and limited secondary market. Subsequently, the framework provides remedy(ies), including but not limited to the use of design to disassemble approach, Waste management and Resource recovery plan, use of multiple bins and setting technical standards for recycled materials. The waste minimisation framework attempts to promote a circular economy in building construction and help academics and industry practitioners to herald a new era of research in sustainable construction. Further, this research is an attempt to contribute to United Nations's Sustainable Development Goal 12 that ensures sustainable consumption of resources by achieving the Target 12.5 (substantially reduce waste generation through prevention, reduction, recycling and reuse).

Keywords: C&D Waste, C&D Waste Minimisation Approaches, Waste Minimisation Framework.

1 Introduction

The increase in infrastructure demand puts the construction sector at the core of the global economy. Construction accounted directly for 6% of global Gross Domestic Product (World Economic Forum, 2017) with the industry being one of the largest in most countries and predicted to grow. The global construction output is forecasted to grow from USD 10.7 trillion in 2020 to 15.2 trillion in 2030 (Oxford Economics,

2021). The construction industry (CI) is an essential feature of any country's overall growth which often comes with concerns such as health and well-being of the community, natural resources consumption, waste, economic growth, and pollution (Presley & Meade, 2010). Social, economic and environmental concerns introduced the need for sustainability in construction (UNEP, 2018).

The definition of SC includes social, economic, and environmental aspects and is deemed a broad concept. This concept gives equal consideration to all aspects and maintains balance throughout the process of construction (UNEP, 2018) and are interdependent. For example, natural resources are extracted from nature for construction, providing employment and economic benefits (Vatalis et al., 2011). Figure 1 shows all three aspects and their interdependency on each other.




Fig.1. Sustainable Construction (Gan et al., 2015)

Application of a life cycle approach in advocating SC to facilitate a circular economy has become a common interest for academics and practitioners in recent years.

The purpose of this research is to find out the state-of-the-art of C&D waste, how it is minimised worldwide, understand waste minimisation challenges and opportunities, its contribution to SC; ultimately, to propose a waste minimisation framework considering the life cycle of a construction project to achieve SC. This aim is achieved through an extensive literature review of journal articles, conference papers, government publications (policies, regulations, etc.), and non-governing organisation's published work.

2 The growing construction and demolition waste issue

Typically, C&D waste is defined as the leftover materials generated during the construction, refurbishment, repair, and demolition of any building (UNEP, 2015). However, the definition of C&D waste varies across the world. For example, countries such as New Zealand, Australia, and Germany consider soil excavated from

contaminated land during land clearance as C&D waste (Brennan et al., 2014), while the USA and Netherlands do not consider excavated soil as a part of C&D waste (European Commission, 2016). Further, in the USA, debris generated due to natural disaster are not considered as a part of the C&D waste (USEPA, 2015). In contrast, countries like Lebanon and Sri Lanka include such debris in their C&D definition (Karunasena, 2012).

In 2000, C&D contributed 3 billion tonnes (BT) to waste generated worldwide (El-Haggag, 2007), and it was the beginning of the recognition of it as an environmental pollution issue. C&D waste has increased since the beginning of this century with, for example, Europe going from 450 million tonnes (MT) per annum in 2005 (Osmani, 2011) to 860 MT in 2010 (Eurostat, 2012) and 900 MT in 2020 (Wu et al., 2022). Similarly, China went from 100 MT at the beginning of this century to outstripping Europe's production in 2014, generating 1.13 BT of C&D waste and became the largest C&D waste generator in the world (USEPA, 2009; CIB, 2011; Wu et al., 2017). These quantities of waste put the environment in danger (CIB, 2011).



Asia-2.5 BT



Europe- 900 MT



North & South America- 800 MT



Australia & NZ- 30 MT

Fig.2. C&D waste in different regions (Wu et al., 2022)

In 2020, Worldwide, more than 10 BT of C&D waste was generated. With over 2.3 BT of C&D waste per year, China was the largest C&D waste producer (Wu et al., 2022). C&D waste produced in Europe was half of Asia and almost similar to North and South America (European Commission, 2020). The South Pacific region (Australia and NZ) combined generated 30 MT (Shooshtarian et al., 2020; MfE, 2021b).

3 C&D waste minimisation and its challenges

C&D waste minimisation is often guided by the need for a sustainable built environment and is a subset of waste management (Domingo & Luo, 2017). The different perspectives to define C&D waste minimisation are considered under two broad categories: i) at source; and ii) by recycling. On-site reuse, reuse and recovery are part of the recycling category (Begum et al., 2007; Gálvez-Martos et al., 2018; Ma et al., 2020). Some of the definitions of waste minimisation from both perspectives are listed in Table 1.

Table 1. Definitions of C&D waste minimisation

By Source	By Recycling	Reference
Design out, reduce or eliminate waste in the design process so there will be none to manage in further stages	Activity to replace consumption of new resources by recycling used ones	Gálvez-Martos et al., 2018
Eliminate waste production in design stage	Reuse or recycling materials to manage waste generated	Ma et al., 2020
Technique or task that reduces or eliminate the waste generation at the source, usually within a process	Recovery and/or reuse of waste generated during and/or after the process.	Begum et al., 2007

The benefits of waste minimisation depend upon how effectively the waste minimisation challenges are addressed. Table 2 overviews C&D waste minimisation challenges during different project stages.

Table 2. Challenges in C&D waste minimisation (Esa et al., 2017; Islam et al., 2019)

Pre-design	Design
Eco-labelling of materials	Material specification writing
Lack of innovation and motivation	Change in scope and design
Early involvement of stakeholders	Waste management plan
Construction	Demolition
Material storage and handling	Regular waste audits
Prefabrication and standardisation	Lack of deconstruction
Waste collection and sorting	Secondary market

The pre-design stage of a project produces a rough estimate of the project and approximate statistics on consumption of both renewable and non-renewable resources (Poon et al., 2004).

The design stage converts ideas into reality, resulting in precise and specific designs of buildings (Gupta et al., 2020). Lack of detailed specification of materials and poor quantity survey of such materials are some of the prime concerns for this stage. The construction stage deals with physical waste resulting from design waste. Construction work needs proper guidance on material storage and handling, which is often considered simple work but performed with poor standards (Esa et al., 2017). Buildings at their end of life are deconstructed or demolished, which result in demolition waste. Demolition projects often don't have a site-specific environment management plans to address issues such as contamination and handling of materials with hazardous substances (Ali et al., 2019). The waste audit covers some of the important factors such as type of building, demolition plans, and cost of demolition.

4 C&D waste minimisation approaches

Modern developments in C&D waste minimisation approaches happened in the last few decades (Domingo, 2011) and variety of instruments has been used since then by industry practitioners (Wu et al., 2019). Worldwide, the approaches are divided into three broad categories: waste management hierarchy; regulations and guidelines; and tools.

4.1 Waste Management Hierarchy

Waste can be generated at any stage (design to end of life) and hence needed more than one option to manage it which introduces waste minimisation or management using a 'Waste Management Hierarchy' (EU, 1975). The waste management hierarchy was the origin of waste minimisation and deemed as mature and commonplace for C&D waste.

All waste hierarchies follow a common pattern of steps with the aim of maximum environmental benefits and minimum waste generation. Figure 3 shows a generalised management hierarchy.




Fig.3. Waste management hierarchy (EU, 1975; UNEP, 2013)

4.2 Guidelines and regulations for C&D waste minimisation

The disposal of C&D waste to landfill was the best-known method to deal with it until the 1980s (UNEP, 2015). As the number of landfills increased worldwide, the negative impact on the environment due to heavy disposal of contaminated soil changed society's perception about landfilling the waste, which introduced need for waste handling and disposal guidelines and regulations (Huang et al., 2018). Table 3 shows the guidelines and regulations used around the world for C&D waste minimisation.

Table 3. Guidelines and regulations for C&D waste minimisation in different regions

Region	Country	Provision for waste minimisation	Regulatory tools
North America	USA	Effective procurement of resources	Waste Reduction Act, 1990
	Canada	Promotion of environmental responsibilities	Canada's Green Plan, 1990
South America	Brazil	Generators responsibilities from design to disposal	Waste Management Resolution (307/2002),
Europe	Europe	Technical guidance for selecting materials	Construction Product Regulations (305/2011)
	UK	A mandatory waste management plan	Site Waste Management Plan Regulations, 2008
Africa	South Africa	Guidelines on material selection and procurement	National Environmental Management Act, 1998
Asia	China	Optimise resource consumption to reduce off-cuts	Construction waste disposal specifications
	India	Ecological design standards for building materials	National Housing and Habitat Policy, 2007
	Japan	Guidelines for selecting construction materials	Ministry of the Environment, 2004
South Pacific	Australia	Sustainable procurement of building materials	Framework for material Procurement, 2007
	New Zealand	Sustainable management of resources	RMA, 1991

4.3 Tools for C&D waste minimisation

Different tools and approaches are used to minimise waste, predict quantities of waste, and forecast recyclable content. For example, a designing out waste tool for buildings helps contractors identify opportunities to prevent waste, record design solutions and calculate their impact on waste (Gupta et al., 2020). Further, the Net Waste Tool focuses on environmental and commercial costs of waste and calculates

the potential waste quantities throughout the project. It also predicts quantities of recyclable material and optimises its consumption (Akinade et al., 2018). Apart from these tools and approaches, several other tools have been used in different parts of the world to minimise C&D waste. Table 4 present some of the widely used tools.

Table 4. Tools for C&D waste minimisation

Tools	Remark	Reference
Lean Tools	Value Stream Mapping and Just in Time are commonly used to control inventory	Vinodh et al., 2011
Supply Chain Management	Controls inventory and creates a smooth flow of information which assists procurement of sustainable building materials.	Vrijhoef & Koskela, 2000
Building Information Modelling	Present a virtual copy of a project and expected physical issues before actual execution. Can be used effectively to design buildings for deconstruction	Moayeri, 2017
Linear Programming	Deals with a single objective function such as minimisation of waste. Output model gives optimised resource consumption	Maués et al., 2020
Vector Optimisation	Target multiple objective functions but is a supportive tool for managing projects.	Rudloff et al., 2017
Dynamic Programming	Future decisions based on the previous decisions. Substantial coding work required.	Zhou et al., 2013

5 Waste minimisation Framework

The review of literature on C&D waste minimisation, helped to develop a waste minimisation framework. It is built on the traditional practices of construction industry and its successful implementation depends on all the personnel (material manufacturer, supplier, contactors, clients, engineers, labours, public bodies, non-governing organizations). The framework identifies C&D waste minimisation challenges over the life cycle of building projects and offers remedial measures. Figure 4 shows the waste minimisation framework for C&D waste.




Fig.4. Waste minimisation framework

6 Conclusions

The profit-driven nature of CI continues to increase the infrastructure demand with sustainability concerns. Despite SC's well-developed definition and understanding, its current status globally, especially through C&D waste minimisation, is far from optimum. C&D waste is growing as an issue worldwide and becoming one of the greatest threats to SC. In addition, state-of-the-art waste minimisation approaches advocating SC throughout the lifecycle remain distant in promoting a circular economy.

C&D waste minimisation challenges occur during all project stages, i.e. pre-design, design, construction, refurbishment and demolition. Some of the key challenges are: poor building standards; lack of waste sorting and assessment, and limited secondary markets for recycled products. To counter the challenges, waste minimisation approaches gave remedies such as: waste management plan; use of BIM; guidelines for reuse and recycling, waste audits and an increase in the waste levy.

Combining waste minimisation challenges and approaches practiced worldwide resulted in a conceptual waste minimisation framework. This framework is built on a life cycle approach and is a comprehensive mechanism to demonstrates the direct relationship between C&D waste minimisation and SC. In addition, the findings of this framework add novelty to the growing body of literature on advocating SC through C&D waste minimisation. This research is an attempt to contribute to United Nations's Sustainable Development Goal 12 that ensures sustainable consumption of resources by achieving the Target 12.5 (substantially reduce waste generation through prevention, reduction, recycling and reuse).

The boundary of this paper offered a standalone perspective on C&D waste minimisation approaches and introduced a conceptual waste minimisation framework. This achievement calls for more studies in this field to integrate and streamline this

framework. In addition, future study could focus on validating the waste minimisation framework through its implementation in different construction contexts.

References

1. Akinade O.O., Oyedele L.O., Ajayi S.O., Bilal M., Alaka H.A., Owolabi H.A. & Arawomo O.O. 2018, 'Designing out construction waste using BIM technology: Stakeholders' expectations for industry deployment', *Journal of Cleaner Production*, vol. 180, pp. 375-85.
2. Ali T., Mert G., Ferhat K., Zhanar B., Aiganym S. & Gulzat S. 2019, 'A Comprehensive Construction and Demolition Waste Management Model using PESTEL and 3R for Construction Companies Operating in Central Asia', *Sustainability*, no. 6, p. 1593.
3. Australian Procurement and Construction Council 2007, *Australian and New Zealand Government Framework for Sustainable Procurement*, The Australian Procurement and Construction Council, Deakin West, ACT, Australia, pp. 1-17,
4. Begum R.A., Siwar C., Pereira J.J. & Jaafar A.H. 2007, 'Implementation of waste management and minimisation in the construction industry of Malaysia', *Resources, Conservation and Recycling*, vol. 51, no. 1, pp. 190-202.
5. Brennan, J. Ding, G. Wonschik, C.-R. & Vessalas, K. 2014, *A Closed-Loop System of Construction and Demolition Waste Recycling The 31st International Symposium on Automation and Robotics in Construction and Mining (ISARC 2014)*, Australia
6. CIB 2011, *Construction Waste Reduction around the World*, Watford, United Kingdom, https://www.irbnet.de/daten/iconda/CIB_DC22829.pdf.
7. DEFRA 2013, *The Site Waste Management Plans Consultation UK Government*, UK, viewed August 18 2019, https://consult.defra.gov.uk/waste/site_waste_management/.
8. Domingo N. 2011, 'Reducing Construction Waste In Healthcare Projects: A project Lifecycle Approach', Loughborough University, UK, <https://dspace.lboro.ac.uk/dspace-jspui/bitstream/2134/9107/1/Thesis-2011-Domingo.pdf>.
9. Domingo N. & Luo H. 2017, 'Canterbury earthquake construction and demolition waste management: issues and improvement suggestions', *International journal of disaster risk reduction*, vol. 22, pp. 130-8.
10. El-Haggar S. 2007, 'Sustainable Industrial Design and Waste Management', *Sustainable Industrial Design and Waste Management*.
11. Esa M.R., Halog A. & Rigamonti L. 2017, 'Strategies for minimizing construction and demolition wastes in Malaysia', *Resources, Conservation and Recycling*, vol. 120, pp. 219-29.
12. EU 1975, 'Council directive', in Union E. (ed.) *Europe*, pp. 1-10, <https://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=CONSLEG:1975L0442:20031120:EN:PDF>.
13. European Commission 2016, *Construction and Demolition Waste European Union*, viewed 27 July 2019, https://en.wikipedia.org/wiki/European_Commission.
14. European Commission 2020, *Construction and demolition waste*, viewed May 6 2022, https://ec.europa.eu/environment/topics/waste-and-recycling/construction-and-demolition-waste_en.
15. Eurostat 2012, *Waste Statistics in Europe*, European Commission, Luxembourg, viewed 29 July 2019, <http://epp.eurostat.ec.europa.eu/>.
16. Gálvez-Martos J.-L., Styles D., Schoenberger H. & Zeschmar-Lahl B. 2018, 'Construction and demolition waste best management practice in Europe', *Resources, Conservation and Recycling*, vol. 136, pp. 166-78.

17. Gan X., Zuo J., Ye K., Skitmore M. & Xiong B. 2015, 'Why sustainable construction? Why not? An owner's perspective', *Habitat International*, vol. 47, pp. 61-8.
18. Government of Canada 1990, 'Canada's Green Plan', in Canada G.o. (ed.), En21-94/1990E, Minister of Supply and Services Canada 1990, Canada, pp. 1-190, <http://cfs.nrcan.gc.ca/pubwarehouse/pdfs/24604.pdf>.
19. Gupta S., Jha K.N. & Vyas G. 2020, 'Proposing building information modeling-based theoretical framework for construction and demolition waste management: strategies and tools', *International Journal of Construction Management*, pp. 1-11.
20. Huang B., Wang X., Kua H., Geng Y., Bleischwitz R. & Ren J. 2018, 'Construction and demolition waste management in China through the 3R principle', *Resources, Conservation and Recycling*, vol. 129, pp. 36-44.
21. Islam R., Nazifa T.H., Yuniarto A., Shanawaz Uddin A.S.M., Salmiati S. & Shahid S. 2019, 'An empirical study of construction and demolition waste generation and implication of recycling', *Waste Management*, vol. 95, pp. 10-21.
22. Karunasena G.I. 2012, 'Capacity building for post disaster waste management : construction and demolition waste', Electronic Thesis or Dissertation, University of Salford, <http://ezproxy.aut.ac.nz/login?url=http://search.ebscohost.com/login.aspx?direct=true&db=edsble&AN=edsble.680473&site=eds-live>.
23. Ma M., Tam V.W., Le K.N. & Li W. 2020, 'Challenges in current construction and demolition waste recycling: A China study', *Waste Management*, vol. 118, pp. 610-25.
24. Maués L.M.F., do Nascimento B.d.M.O., Lu W. & Xue F. 2020, 'Estimating construction waste generation in residential buildings: A fuzzy set theory approach in the Brazilian Amazon', *Journal of Cleaner Production*, vol. 265, p. 121779.
25. Ministry of Housing and Urban Affairs 2018, Strategy for Promoting Processing of Construction and Demolition (C&D) Waste and Utilisation of Recycled Products, Government of India, Delhi, India, pp. 1-40,
26. Ministry of Housing and Urban Rural Development 2010, The industry standard of the People's Republic of China (CJJ 134-2009 Record No. J 960-2009): Construction waste disposal technical specifications, Government of China, People's Republic of China, <https://www.abebooks.com/industry-standard-Peoples-Republic-China-CJJ/14929682686/bd>.
27. Ministry of the Environment 2004, Waste Management and Recycling in Japan, Government of Japan, Japan, pp. 1-24
28. Moayeri V. 2017, 'Design Change Management in Construction Projects Using Building Information Modeling (BIM)', Concordia University, Montreal, Quebec, Canada, <https://pdfs.semanticscholar.org/1865/9bdbef5887d4c4e0d1f14ebd5dba32fbaecf.pdf>.
29. National Environment Council 2002, Resolution Number 307, Ministry for the Environment, Brazil, pp. 1-4, https://www.mma.gov.br/estruturas/a3p/_arquivos/36_09102008030504.pdf.
30. National Environmental Management Act 1998, 'National Environmental Management Act 107 of 1998 ', Government of South Africa, Cape Town, South Africa, <https://cer.org.za/wp-content/uploads/2014/02/NEMA-107-of-1998.pdf>.
31. Osmani M. 2011, Construction waste.
32. Oxford Economics 2021, Future of Construction, Oxford Economics Group, viewed June 25 2022, <https://www.oxfordeconomics.com/resource/future-of-construction/>.
33. Poon C.S., Yu A.T.W. & Jaillon L. 2004, 'Reducing building waste at construction sites in Hong Kong', *Construction Management and Economics*, vol. 22, no. 5, pp. 461-70.
34. Presley A. & Meade L. 2010, 'Benchmarking for sustainability: application to the sustainable construction industry', vol. 17, no. 3.

35. RMA 1991, Resource Management Act, New Zealand, <http://www.legislation.govt.nz/act/public/1991/0069/latest/whole.html#DLM236746>.
36. Rudloff B., Ulus F. & Vanderbei R. 2017, 'A parametric simplex algorithm for linear vector optimization problems', *Mathematical Programming*, vol. 163, no. 1-2, pp. 213-42.
37. Shoosharian S., Maqsood T., Wong P.S. & Khalfan M. 2020, 'Market development for a construction and demolition waste stream in Australia', *Journal of Construction Engineering*, vol. 3, no. 3, pp. 220-31.
38. UNEP 2013, Guidelines for National Waste Management Strategies: Moving from Challenges to Opportunities, United Nations Environment Programme and the United Nations Institute for Training and Research, http://cwm.unitar.org/national-profiles/publications/cw/wm/UNEP_UNITAR_NWMS_English.pdf.
39. UNEP 2015, Global Waste Management Outlook (GWMO), United Nations-International Environmental Technology Centre, <https://www.uncclearn.org/sites/default/files/inventory/unep23092015.pdf>.
40. UNEP 2018, Programme Performance Report 2019, United Nations, Switzerland, https://wedocs.unep.org/bitstream/handle/20.500.11822/27734/PPR_2018_FINAL.pdf?sequence=1&isAllowed=y.
41. USEPA 2009, Construction and demolition materials amounts, USA, pp. 1-60, <https://www.epa.gov/sites/production/files/2017-09/documents/estimating2003buildingrelatedcanddmaterialsamounds.pdf>.
42. USEPA 2015, Construction and Demolition:Material-Specific Data, United States Government, USA, viewed July 27 2019, <https://www.epa.gov/facts-and-figures-about-materials-waste-and-recycling/construction-and-demolition-material-specific>.
43. Vatalis K.I., Manoliadis O.G. & Charalampides G. 2011, 'Assessment of the economic benefits from sustainable construction in Greece', *International Journal of Sustainable Development & World Ecology*, vol. 18, no. 5, p. 377.
44. Vinodh S., Arvind K. & Somanathan M. 2011, 'Tools and techniques for enabling sustainability through lean initiatives', *Clean Technologies and Environmental Policy*, vol. 13, no. 3, pp. 469-79.
45. Vrijhoef, R. & Koskela, L. 2000, "The four roles of supply chain management in construction", *European Journal of Purchasing & Supply Management*, Vol 6, Issue 3-4, pp. 169-178.
46. Waste Reduction Act 1990, 'House Resolution 1457 — 101st Congress: Waste Reduction Act', in Agency U.E.P. (ed.)US Government, USA, <https://www.govtrack.us/congress/bills/101/hr1457>.
47. World Economic Forum 2017, China's clean, green buildings of the future, viewed 17 June 2019, <https://www.weforum.org/agenda/2017/06/china-clean-green-buildings-future/>.
48. Wu H., Zuo J., Yuan H., Zillante G. & Wang J. 2019, 'A review of performance assessment methods for construction and demolition waste management', *Resources, Conservation and Recycling*, vol. 150, p. 104407.
49. Wu Z., Yang K., Xue H., Zuo J. & Li S. 2022, 'Major barriers to information sharing in reverse logistics of construction and demolition waste', *Journal of Cleaner Production*, vol. 350, p. 131331.
50. Zhou J., Love P.E., Wang X., Teo K.L. & Irani Z. 2013, 'A review of methods and algorithms for optimizing construction scheduling', *Journal of the Operational Research Society*, vol. 64, no. 8, pp. 1091-105.

Open Access This chapter is licensed under the terms of the Creative Commons Attribution-NonCommercial 4.0 International License (<http://creativecommons.org/licenses/by-nc/4.0/>), which permits any noncommercial use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license and indicate if changes were made.

The images or other third party material in this chapter are included in the chapter's Creative Commons license, unless indicated otherwise in a credit line to the material. If material is not included in the chapter's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder.

