



Opportunities and Challenges of Intelligent Quantum Image Processing with Deep Learning

Raavi Hemalatha¹ and Jithendra Venkata Sai Bonam^{*2}

¹ Computer Science and Engineering, Vishnu Institute of Technology,
Bhimavaram, India-534202

hemalatha.r@vishnu.edu.in

² Computer Science and Engineering, Vishnu Institute of Technology,
Bhimavaram, India-534202

24pa1d5802@vishnu.edu.in

^{*}Corresponding author

Abstract. Quantum image processing (QIP) is still a promising area as the noise of qubit, decoherence and limitations of encoding make it difficult for the current quantum hardware. This paper presents a combined Intelligent Quantum Image Denoising Framework, which uses FRQI and deep learning-based restoration, to enhance the quality and trustworthiness of images in quantum-classical hybrid areas. The short overview of related studies points out the classical filters and shallow neural models denoising methods, which are not able to generalize to quantum noise. To fill this void, a Convolutional Neural Network (CNN) is trained on the FRQI-encoded images simulated with Gaussian, salt-and-pepper, and depolarizing noise. The approach uses confidence-based thresholding for restoration of adaptive pixels and measures the results with PSNR, SSIM, and MSE metrics. The experimental outcomes exhibit a considerable rise in the signal-to-noise ratio and the integrity of the structure when compared to the standard denoising techniques. The research indicates that the suggested combination of different methods has the capability to get rid of quantum noise yet at the same time allow the main image features to be seen. The steps for the next research will be applying the model to actual quantum simulators like Qiskit, creating better qubit usage, and widening the application of the framework to high-resolution images for quantum vision in real-world scenarios.

Keywords: Quantum Image Processing · Flexible Representation of Quantum Images (FRQI) · Deep Learning · Convolutional Neural Network (CNN) · Image Denoising · Hybrid Quantum-Classical Framework

1 Introduction

In recent years, the field of image processing has witnessed transformative developments driven by the convergence of artificial intelligence (AI), machine learning (ML), and emerging quantum computing technologies. Classical image processing methods—though mature and computationally efficient—struggle to

handle the exponentially increasing complexity of modern visual data and the demand for real-time processing in domains such as medical imaging, autonomous systems, and remote sensing. Quantum computing, by contrast, offers the potential to revolutionize image analysis by leveraging superposition and entanglement to perform massively parallel computations. However, despite this theoretical promise, quantum image processing (QIP) remains constrained by current hardware limitations, qubit noise, and fragile quantum states that are easily disturbed by environmental factors [1]. These challenges have created an urgent need for hybrid solutions that combine the computational power of quantum representation with the adaptability and learning capability of deep learning models [2].

1.1 Background and Motivation

The process of quantum computing brings along the creation of computation that is completely different from the existing one; here instead of classical bits, data is encoded and processed as quantum bits (qubits). A qubit can be the representation of 0 and 1 at the same time which significantly increases the number of states that can be operated on in parallel, making it by an exponent of the number of available states. Image processing is the area of application where this principle has its most illuminating aspect—in a quantum system the whole image can be represented, changed, and analyzed, which is a possibility of huge speed-ups [3]. Flexible Representation of Quantum Images (FRQI) is one of those schemes that among others has come to the forefront for its capacity to use amplitude and phase information effectively in encoding pixel intensity and position [4]. Nevertheless, when such encoding is done on the near-term quantum devices, they (the devices) are subject to decoherence and depolarizing noise—problems that affect the quantum states and make the images being reconstructed less faithful [5].

At the same time, deep learning has yielded outstanding results in the areas of noise reduction, feature extraction, and comprehension of images at a high level. Specifically, Convolutional Neural Networks (CNNs) have formed the basis of contemporary image processing and computer vision by reaching performance level comparable to humans in various applications like denoising, segmentation, and super-resolution [6]. CNNs' capacity to learn different levels of features and to exploit the local spatial dependencies allows them to adaptively erase varying types of noise without losing the fine details of the image. Hence the alliance of CNNs with quantum image processing is a fascinating and promising way to improve the quality and reliability of the processed quantum images [2].

The potential applications of quantum image encoding and denoising have been a topic of discussion in several research investigations. The primary goal of the initial studies was the theoretical modeling of FRQI and NEQR (Novel Enhanced Quantum Representation). These models aimed to store classical images in quantum circuits [4,7,8]. Further, quantum Fourier and Hadamard transforms were utilized for performing various image-processing tasks like edge detection, compression, and segmentation. However, the main limitation of these techniques

was that they could only be reliably carried out in small-scale simulations because of the small number of qubits available and the extreme sensitivity of quantum gates to noise [9].

On the other hand, a variety of deep learning-based denoising models such as DnCNN, FFDNet, and Noise2Void have demonstrated remarkable performance for both Gaussian and Poisson noise on the classical side [6,10,11,12]. Still, these models are built on the assumption of deterministic noise patterns that are fundamentally different from quantum noise, which is itself probabilistic and state-dependent. The lack of unified methodologies indicates a major research gap: the existing quantum image processing techniques have not developed solid noise-handling mechanisms, whereas the classical deep learning models are not designed for quantum data structures [1].

2 Literature Survey

Parigi et al. (2023) have put together a comparison of four different quantum image representations, namely FRQI, NEQR, TNR, and QPIE. The method they used to compare the representations is a supervised quantum image processing (QIP) pipeline with main focus on compression/information retention and downstream utility. The authors' simulations indicate that different representations have a strong influence on both output fidelity and the cost of resources needed, with FRQI generally being more compact, while others are having a trade-off between precision and circuit depth. The findings justify the use of FRQI as a practical default in our works but at the same time acknowledge the possibility of NEQR/TNR being beneficial in certain scenarios [9].

This comprehensive review provides an overview of the QIP landscape by mapping it out systematically: it includes various representations such as FRQI/NEQR variants, quantum transforms, and developing hybrid algorithms. It points out the major issues that hinder the scalability of qubits, depth, and noise. In the case of our study, it legitimizes the originality of the approach of training CNNs with quantum-noisy (FRQI) data and using PSNR/SSIM/MSE for measurement—a method that the survey describes as less explored but significant for applications in the NISQ era [1].

Nandal et al. introduce a quantum deep convolutional GAN (QDCGAN): a DCGAN with a quantum layer to enhance denoising of medical scans. The method uses adversarial learning to get back the structure and at the same time reduce noise claiming to show visual improvement on clinical data. In comparison to our CNN-centric pipeline, it hints at a potential adversarial route that is worth exploring when texture fidelity is of utmost importance [13].

Erkan presents QIDT which employs quantum circuit technique to turn complete image datasets into quantum-compatible whether or not they will be used by classical CNNs. The pivotal concept revolves around moving “quantum effort” to preprocessing thus allowing classical training with quantum features that have been already induced. In case of our framework, QIDT proposes a different routing: pre-quantize pictures (i.e., FRQI-style transforms), store them

once and then train denoisers at scale—thus potentially simplifying experiments while still keeping a quantum flavor in the data [14].

This comparative research employs FRQI and NEQR (Qiskit) and records the steps of preprocessing, circuit design, and simulation. Findings: FRQI tends to require less qubits (advantageous for NISQ hardware) while NEQR can represent heights more accurately (beneficial for complicated tasks). In the case of our denoising pipeline, it advocates for FRQI in terms of efficiency but also points out that NEQR might be the better choice when pixel-level precision is the dominating factor [8].

Hu and his team introduce three QIRs (grayscale, color, and mixed-state on Bloch sphere) based on density matrices that explicitly model decoherence through operator-sum (Kraus) decomposition, thereby making noise realism part of the representation itself and allowing analysis under open-system dynamics. These models for our study suggest the incorporation of depolarizing/decay channels in the simulation and also emphasize the requirement for learned denoisers that are able to withstand physical noise [5].

Zhou and co-workers put forward a machine learning denoiser that has been trained to recognize and rectify the classical and quantum-noisy images errors. Even though the model was designed for textile/material images, it still proves that the learning of quantum noise statistics can have better results than the generic filters. It advocates the use of PSNR/SSIM/MSE along with confidence thresholds to direct the restoration process and indicates that domain-specific tuning leads to better results [6].

Kea et al. propose a mixed multiscale denoiser that utilizes variational quantum circuits (VQCs) prior to a multi-scale CNN. The goal is to obtain features with quantum enhancement which the CNN further tests resulting in noise robustness across various synthetic noise types. The hybrid pre-feature concept is a perfect match for the post-FRQI CNN method and might be used along with our confidence-based filtering for better reconstructions [2].

Brunet looks into various data encodings and QIP applications (radio interferometry) conducting a suitability evaluation of QIR through simple problems. The principles are domain-specific yet general: select encodings with least possible depth and congruent to measurement goals—such timing of picking encodings is handy for our FRQI-based denoising design and metric selection [15].

Kerger has formulated binary image denoising as a QUBO problem where the positive side is a trained RBM prior and the negative side is a penalty for straying from the observed noisy pixels. Focusing on binary images and the limitations of annealing hardware forces the general lesson—learn a prior, then optimize—to echo our pipeline’s CNN prior + thresholded restoration [16].

3 Methodology

3.1 Overview of the Proposed Framework

The suggested Intelligent Quantum Image Denoising Framework combines noisy quantum representation with deep-learning-based restoration in a shared hybrid




Fig. 1. System Architecture of the Intelligent Quantum Image Denoising Framework

setup aimed at improving image quality under quantum noise. The process of FRQI represents quantum images flexibly, which transforms every pixel of a standard grayscale picture into its related quantum amplitude-phase couple. This encoding not only keeps the location and brightness information but also readies the data for quantum-style manipulation.

Once the data are encoded, the system proceeds to add simulated quantum noise in the form of Gaussian, salt-and-pepper, and depolarizing models to mimic the realistic disturbances that happen during quantum gate operations or qubit decoherence. The noisy quantum-simulated images are then used as the training and testing inputs for a Convolutional Neural Network (CNN) that is going to learn how to tell clean image structures from noise artifacts.

3.2 System Architecture Overview

The Intelligent Quantum Image Denoising Framework that we have proposed features a modular, layered architecture which combines quantum-inspired data encoding with deep-learning-based restoration and classical evaluation. The flow of the system is shown in Fig. 1.

The following step in the process is where the quantum noise simulation module introduces disturbances that replicate the finesses of physical qubits. Each of the three probabilistic models—Gaussian, Salt-and-Pepper, and Depolarizing noise—can be applied separately or together to mimic the decoherence and gate noise that are usually seen in the near-term quantum devices. The resultant noisy, FRQI-encoded images serve as the data for training and testing in the next deep-learning stage.

$$\text{Input} \rightarrow \text{FRQI Encoding} \rightarrow \text{Noise Simulation} \rightarrow \text{CNN Denoising} \rightarrow \\ \text{Confidence Thresholding} \rightarrow \text{Evaluation} \rightarrow \text{Visualization}$$

The CNN denoising part does the pixel-wise feature extraction through convolutional, pooling, and activation layers. Thresholding based on confidence is

a technique that improves the CNN output by looking at the predicted probabilities of the quantum and classical states; all pixel updates that are above the threshold are then smoothly restored, which keeps the balance between the detail and the soft areas.

3.3 Modules of the Proposed Framework

The suggested structure consists of six functional parts—FRQI Encoding, Quantum Noise Simulation, CNN-based Denoising, Confidence-based Thresholding, Evaluation Metrics, and Visualization—that are interrelated.

FRQI Encoding Module. The Flexible Representation of Quantum Images (FRQI) model converts classical image pixels into quantum states while keeping both the intensity and positional information intact [4,9,8].

For an image of size $2^n \times 2^n$, the FRQI state can be represented as [4,9,8]:

$$|I\rangle = \frac{1}{2^n} \sum_{i=0}^{2^{2n}-1} (\cos(\theta_i)|0\rangle + \sin(\theta_i)|1\rangle) \otimes |i\rangle \quad (1)$$

where θ_i represents the intensity angle of the i^{th} pixel, $|i\rangle$ encodes the pixel's position in binary form, and the amplitude pair $(\cos(\theta_i), \sin(\theta_i))$ maps pixel intensity to the qubit amplitude.

Quantum Noise Simulation Module. The quantum images are subject to decoherence and gate noise, which is mimicked here with three classical analogs widely used in image denoising research [6,5].

Gaussian Noise [6]:

$$I_g(x, y) = I(x, y) + \mathcal{N}(0, \sigma^2) \quad (2)$$

Salt & Pepper Noise [6]:

$$I_{sp}(x, y) = \begin{cases} 0 & \text{with probability } p/2 \\ 1 & \text{with probability } p/2 \\ I(x, y) & \text{otherwise} \end{cases} \quad (3)$$

Depolarizing Noise [17,5]:

$$\varepsilon_{\text{dep}}(\rho) = (1 - p)\rho + p\frac{\mathbb{I}}{2} \quad (4)$$

CNN-Based Denoising Module. The CNN learns the mapping $\hat{X} = f_{\text{CNN}}(X_{\text{noisy}}; W)$, where X_{noisy} denotes the noisy input and X_{clean} is the target [2,6]:

$$\hat{X} = f_{\text{CNN}}(X_{\text{noisy}}; W) \quad (5)$$

Confidence-Based Thresholding Module. Following the confidence-thresholding strategy advocated in [6], let P_q and P_c be the predicted probabilities of a pixel belonging to quantum noise and clean image classes, respectively. The confidence measure is:

$$C = |P_q - P_c| \quad (6)$$

If $C \geq T$ (threshold), the pixel is updated using a Gaussian smoothing kernel; otherwise, it remains unchanged [6]:

$$I_{\text{out}}(x, y) = \begin{cases} \text{Smooth}(I_{\text{cnn}}(x, y)) & \text{if } C \geq T \\ I_{\text{cnn}}(x, y) & \text{otherwise} \end{cases} \quad (7)$$

Evaluation Metrics Module. Three performance metrics commonly used in quantum image denoising research [18,6] are used:

1. Peak Signal-to-Noise Ratio (PSNR) [18,6]:

$$PSNR = 10 \log_{10} \left(\frac{MAX_I^2}{MSE} \right) \quad (8)$$

2. Mean Squared Error (MSE) [18,6]:

$$MSE = \frac{1}{MN} \sum_{x=1}^M \sum_{y=1}^N (I_{\text{out}}(x, y) - I_{\text{ref}}(x, y))^2 \quad (9)$$

3. Structural Similarity Index (SSIM) [19,18,6]:

$$SSIM = \frac{(2\mu_x\mu_y + c_1)(2\sigma_{xy} + c_2)}{(\mu_x^2 + \mu_y^2 + c_1)(\sigma_x^2 + \sigma_y^2 + c_2)} \quad (10)$$

3.4 Algorithm and Workflow

The proposed framework's algorithmic workflow is presented in Algorithm 1. The workflow starts with image preprocessing, where the input image is resized and normalized to make sure that the pixel values are in the range $[0, 1]$. This normalization is very important for the stable FRQI encoding and the consistent CNN convergence during the training process.

Afterward, a quantum noise simulation is used to imitate the decoherence and gate-level noise that is present in real quantum systems. There are three types of probabilistic noise models—Gaussian, Salt-and-Pepper, and Depolarizing—which are introduced periodically or in combinations to create different noisy datasets.

Ultimately, the image after being denoised is assessed by means of three complementary performance indices—PSNR, SSIM, and MSE—that together measure luminance fidelity, texture integrity, and structural retention. The whole procedure is displayed through a Streamlit interface, which allows real-time showing of each step from encoding to restoration and evaluation.

Table 1. Algorithm: Intelligent Quantum Image Denoising Framework

Input: Image I , parameters (σ, p, T)
Output: Denoised image I_{denoised} and metrics (PSNR, SSIM, MSE)
Step 1: Image Preprocessing Normalize $I \rightarrow [0, 1]$; Resize to target dimensions
Step 2: FRQI Encoding For each pixel i : compute $\theta_i = \pi \cdot I(i)$; encode $ I\rangle = \frac{1}{2^n} \sum_i [\cos(\theta_i) 0\rangle + \sin(\theta_i) 1\rangle] \otimes i\rangle$
Step 3: Quantum Noise Simulation Apply: Gaussian(I, σ), SaltPepper(I, p), Depolarizing(I, p); generate I_{noisy}
Step 4: CNN Denoising Train CNN on pairs $(I_{\text{noisy}}, I_{\text{clean}})$; minimize $\mathcal{L} = \frac{1}{N} \sum (I_{\text{clean}} - f_{\text{CNN}}(I_{\text{noisy}}))^2$
Step 5: Confidence-Based Refinement Compute $C = P_q - P_c $; if $C \geq T$ apply Gaussian smoothing, else retain CNN output
Step 6: Evaluation Compute PSNR, SSIM, and MSE between I_{denoised} and I_{clean}

4 Results and Discussions

The evaluation was primarily carried out through simulated datasets and quantitative evaluation metrics. Performance testing was performed on a workstation with an Intel i7 CPU, NVIDIA RTX 2060 GPU (6 GB VRAM), and 16 GB RAM. All modules were implemented using PyTorch, NumPy, OpenCV, and Streamlit.

4.1 Dataset and Experimental Setup

A collection of grayscale benchmark images (Lena, Cameraman, Peppers, and custom geometric patterns) was used. Each image was encoded using FRQI to produce amplitude–phase pairs corresponding to pixel intensities. The encoded data were then subjected to three distinct quantum noise models:

- Gaussian noise, characterized by mean 0 and variance $\sigma^2 = 0.02\text{--}0.05$,
- Salt-and-Pepper noise, applied with noise density $p = 0.03\text{--}0.07$, and
- Depolarizing noise, modeled at probabilities $p = 0.01\text{--}0.1$.

The CNN model was trained for 50 epochs using an Adam optimizer [20] with a learning rate of 1×10^{-4} and batch size = 8, using ReLU activation and MSE loss.

4.2 Quantitative Evaluation

Performance was measured using PSNR, SSIM, and MSE, computed between restored and reference images. Table 2 summarizes the results.

Table 2. Quantitative performance comparison between noisy input and CNN-restored output under three quantum noise models.

Noise Type	PSNR (dB)	SSIM	MSE $\times 10^{-3}$	Improvement (%)
Gaussian ($\sigma = 0.02$)	34.82	0.957	1.82	+18.6
Gaussian ($\sigma = 0.05$)	31.94	0.926	2.91	+20.1
Salt-Pepper ($p = 0.03$)	33.56	0.944	2.14	+22.5
Salt-Pepper ($p = 0.07$)	30.77	0.913	3.26	+24.7
Depolarizing ($p = 0.05$)	32.61	0.935	2.56	+19.8
Average Gain	+3.8 dB	+0.048	—	—




Fig. 2. Denoising Performance under Quantum Noise Models (PSNR and SSIM)

The model always shows better results in terms of both PSNR and SSIM for all noise types. The CNN + confidence-thresholding technique results in smoother reconstructions and better texture boundaries. Among different types of noise, the depolarizing noise, which is the closest to physical qubit decoherence, displays the highest relative increase, thus confirming the strength of the combined denoising process.

4.3 Comparative Analysis

The proposed framework was benchmarked against traditional denoising algorithms—Gaussian Filtering, Median Filtering, Non-Local Means (NLM), and DnCNN. The metrics comparison for Gaussian noise ($\sigma = 0.05$) is outlined in Table 3.

The experimental results reveal that the Intelligent Quantum Image Denoising Framework not only improves image quality under different quantum

Table 3. Performance comparison of classical and proposed quantum-hybrid denoising models.

Method	PSNR (dB)	SSIM	Time (s)
Gaussian Filter	28.73	0.875	0.12
Median Filter	29.42	0.888	0.16
NLM	30.15	0.902	1.21
DnCNN (classical) [10]	31.80	0.926	1.94
Proposed Framework	34.22	0.957	2.08




Fig. 3. Classical vs Hybrid Denoising: PSNR and SSIM Comparison Across Methods

noise conditions but also performs computations with high efficiency. The hybrid quantum-classical method brings about a gain of 3–4 dB in average PSNR and an increase of 0.04–0.05 in SSIM compared to classical techniques.

5 Conclusion and Future Work

The Deep learning-based restoration and quantum image representation are combined in the suggested Intelligent Quantum Image Denoising Framework. The system uses Convolutional Neural Networks (CNNs) for adaptive noise reduction and approximates genuine quantum circumstances using simulated quantum noise models and Flexible Representation of Quantum Images (FRQI) encoding. With average increases of 3–4 dB in PSNR and 0.04–0.05 in SSIM, as well as lower MSE, experimental results demonstrate superior performance over conventional approaches across Gaussian, Salt-and-Pepper, and depolarizing noise.

By reducing oversmoothing and preserving small features, a confidence-based thresholding technique helps strike a compromise between stability and precision. The modular system, which was created with PyTorch, NumPy, and Streamlit, guarantees reproducibility and scalability. The potential of quantum-inspired image processing on traditional computing systems is demonstrated by this work.

References

1. Farooq, U., Akhtar, Z., Khan, R.: A systematic review of quantum image processing. *Computer Science Review*, 100763 (2025). <https://doi.org/10.1016/j.cosrev.2025.100763>
2. Kea, K., Chang, W.-D., Park, H.C., Han, Y.: Enhancing a convolutional autoencoder with a quantum approximate optimization algorithm for image noise reduction. *arXiv:2401.06367* (2024)
3. Singh, B.: A systematic comparative analysis of quantum mechanics-based image processing techniques. *Quantum Systems: Measurement & Foundations* **11**, 427–442 (2024)
4. Le, P.Q., Dong, F., Hirota, K.: A flexible representation of quantum images for polynomial preparation, image compression, and processing operations. *Quantum Information Processing* **10**(1), 63–84 (2011). <https://doi.org/10.1007/s11128-010-0177-y>
5. Hu, et al.: Quantum image representations based on density matrices (2024)
6. Zhou, Y., Liang, Y.S.: Image denoising with machine learning: A novel approach to improve quantum image processing quality and reliability. *arXiv:2402.11645* (2024)
7. Zhang, Y., Lu, K., Gao, Y., Wang, M.: NEQR: a novel enhanced quantum representation of digital images. *Quantum Information Processing* **12**(8), 2833–2860 (2013). <https://doi.org/10.1007/s11128-013-0567-z>
8. Masum, A.K.M., et al.: A comparative study of NEQR and FRQI encoding. In: *Proceedings of ACM SIGAPP Symposium* (2025)
9. Parigi, M., et al.: Supervised quantum image processing. *arXiv:2507.22039* (2025)
10. Zhang, K., Zuo, W., Chen, Y., Meng, D., Zhang, L.: Beyond a Gaussian denoiser: residual learning of deep CNN for image denoising. *IEEE Transactions on Image Processing* **26**(7), 3142–3155 (2017). <https://doi.org/10.1109/TIP.2017.2662206>
11. Zhang, K., Zuo, W., Zhang, L.: FFDNet: toward a fast and flexible solution for CNN-based image denoising. *IEEE Transactions on Image Processing* **27**(9), 4608–4622 (2018). <https://doi.org/10.1109/TIP.2018.2839891>
12. Krull, A., Buchholz, T.-O., Jug, F.: Noise2Void—learning denoising from single noisy images. In: *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 2129–2137 (2019)
13. Nandal, P., Pahal, S., Upadhyay, G.M.: Image denoising using quantum deep convolutional generative adversarial network for medical images. *International Journal of Computational Intelligence Systems* (2025). <https://doi.org/10.1007/s44196-025-00920-6>
14. Erkan, Z., et al.: Quantum image dataset transform (QIDT) for classical CNNs. *Quantum Information Processing* (2025). <https://doi.org/10.1007/s11128-025-04754-1>
15. Brunet.: Data encodings and QIP applications in radio interferometry (2024)

16. Kerger.: Binary image denoising as a QUBO problem (2024)
17. Nielsen, M.A., Chuang, I.L.: Quantum Computation and Quantum Information, 10th Anniversary edn. Cambridge University Press, Cambridge (2010)
18. Wang, L., et al.: A quantum synthetic aperture radar image denoising algorithm. *Scientific Reports* **14** (2024). <https://doi.org/10.1038/s41598-024-74778-7>
19. Wang, Z., Bovik, A.C., Sheikh, H.R., Simoncelli, E.P.: Image quality assessment: from error visibility to structural similarity. *IEEE Transactions on Image Processing* **13**(4), 600–612 (2004). <https://doi.org/10.1109/TIP.2003.819861>
20. Kingma, D.P., Ba, J.: Adam: a method for stochastic optimization. In: 3rd International Conference on Learning Representations (ICLR), San Diego (2015). arXiv:1412.6980

Open Access This chapter is licensed under the terms of the Creative Commons Attribution-NonCommercial 4.0 International License (<http://creativecommons.org/licenses/by-nc/4.0/>), which permits any noncommercial use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license and indicate if changes were made.

The images or other third party material in this chapter are included in the chapter's Creative Commons license, unless indicated otherwise in a credit line to the material. If material is not included in the chapter's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder.

