



# Generative AI-Driven Synthetic Data Augmentation for Addressing Class Imbalance in Machine Learning Models

Errolla Pragnya<sup>\*1</sup>, Kuppam Akash<sup>2</sup> and Reema Lalit<sup>3</sup>

<sup>1\*</sup> AIT-CSE, Chandigarh University, Mohali-140413, Punjab, India  
\*pragnyaraj654@gmail.com

<sup>2</sup> AIT-CSE, Chandigarh University, Mohali-140413, Punjab, India  
ka5274382@gmail.com

<sup>3</sup> AIT-CSE, Chandigarh University, Mohali-140413, Punjab, India  
reema.lalit@gmail.com

**Abstract.** Class imbalance has been a challenging phenomenon for supervised learning, resulting in biased classifiers that are biased towards the majority classes and show poor performance for minority classes. This paper presents a Generative AI-based synthetic data augmentation framework that attempts to alleviate the effects of imbalanced data. This approach exploits the capabilities of deep generative learning techniques, such as GANs and VAEs, for the generation of synthetic data for minority classes. This framework combines data preprocessing, generative model training, synthetic data validation, and model retraining into a single Python-based framework. Experiments conducted with the proposed approach show significant improvements in metrics such as precision, recall, F1-score, and balanced accuracy, along with a reduction in the overall bias towards majority classes. When compared with traditional resampling methods, the generative model-based synthetic data augmentation shows better generalization and robustness. This demonstrates the potential for the development of synthetic data generation techniques for improving the overall performance and fairness of imbalanced machine learning classifiers.

**Keywords:** Generative Artificial Intelligence, Synthetic Data Augmentation, Class Imbalance, Generative Adversarial Networks (GANs), Variational Auto-encoders (VAEs), Minority Class Enhancement, Machine Learning, Bias Reduction, Deep Learning, Model Generalization.

## 1 Introduction

The issue of class imbalance is so widespread in monitored machine learning, with many more samples of one category compared to the rest of the classes. This imbalance can predictively model bias, which is to the advantage of majority classes and disadvantage to minority classes, especially at the point of high risk, like medical diagnosis, detect fraud, cybersecurity, and fault prediction [1] [2]. Conversely, the

traditional classifiers befriend overall accuracy hence obscurant poor minority-class detection. Performance such metrics, including precision, recall, F1-score, and balanced accuracy have therefore been introduced as the cycle metrics in imbalanced learning situations [3] [4]. Traditional solutions to the problem of class imbalance comprise both data-level solutions (random oversampling, random undersampling, and Synthetic Minority Over-sampling Technique (SMOTE)) and algorithm-level solutions (cost-sensitive learning and weighted loss functions) [5] [6] [7]. Although the methods can be used to enhance recognition ability of the minority classes to a certain degree, these methods are typically characterized by drawbacks such as overfitting, loss of information, or low diversity in synthetic samples [8] [9]. Moreover, plain resampling schemes might be ineffective to represent the intricate data distributions of high-dimensional feature spaces, especially of high-dimensional image, text, and sensor-based datasets [10] [11]. The latest developments in the field of deep learning provided the possibility of learning a complex set of data with the help of generative models and producing real-like synthesized samples. The Generative Adversarial Networks (GANs) have shown a high level of success in generating high-quality synthetic data by training a generator and discriminator under an adversarial environment [12] [13]. On the same note, Variational Autoencoders (VAEs) extend that systematic learning and data to latent space offer a probabilistic framework [14] [15]. These generative methods have a major benefit compared to classical oversampling techniques of recovering underlying data manifolds and generate a rich and high fidelity samples [16]. Imbalanced learning with the application of generative AI has turned out to be a promising field of research. Generative models can improve the representation of the classes by creating synthetic minority class samples that are highly similar to the original real data [17] [18]. Such method is not only more sensitive to classifier to minority categories but also better able to be generalized to unseen data distribution. In addition, architecture and design hybrid architectures that integrate both GANs and VAEs have been considered to take advantage of the capabilities in both adversarial and probabilistic learning paradigms [19]. In spite of such developments, these innovations have a number of challenges posed on the continuation of generative data augmentation to be utilized in real-world settings. Other problems include mode collapse with GANs, the instability of the latent space with VAEs, the way the training is based on a more complex problem, the computational cost, and the authenticity of the results from synthetic data should be properly considered [20]. Moreover, the acceptance of the fact that synthetic data does not become noisy, generates bias, or poses an unethical threat is an important issue when applying it into practice [21]. Thus, evaluation frameworks based on systematic evaluation are needed to confirm the effectiveness of generative augmentation strategies.

This study presents a Generative AI-based synthetic data augmentation model that is customized to alleviate the impact of class imbalance in the process of performing supervised learning. The presented system combines data preprocessing, training a generative model, synthetic validation of samples, and re-training classifiers and makes them a single pipeline, which is executed with help of machine learning workflows written in Python. The framework will enhance performance in terms of

classification, the decrease in discrimination of majority classes, and the generalization of the models in order to create a realistic minority sample using the help of GANs and VAEs. The research offers empirical assessment and the comparative analysis to show how the proposed solution was effective to solve the imbalanced dataset predicament.

2 Literature Review

The current literature shows that the issue of class imbalance still prevails in the biomedical, financial, and engineering research areas, and the sophisticated element of augmentation and hybrid deep learning approaches is implemented. Hybrid LSTM-KAN has been shown to perform notably better on respiratory sound classification on non-uniform distributions in healthcare analytics [1], whereas explainable TabNet transformers are better at detecting stress based on physiological signals [2]. The use of GAN-based augmentation has been found to work in the classifications of financial statements [3], MRI brain tumors [5], the detection of heart sound abnormalities [8], and in leaf disease detection using hybrid VGGNet–ViT systems [21]. In the same way, stochastic gradient descent-based activation mapping and augmentation can be used to detect multi-class skin cancer [4], and mixup with EfficientNet can be used to increase the resilience of dermatological classification [16]. The modified super pixel segmentation with optimised Adam tuning is proven to be precise in breast cancer diagnosis [7], and the frameworks of dental caries localisation, like DCDNet, extends automated oral diagnostics [13]. All of these works demonstrate that hybrid architectures and synthetic data generation reinforce predictive reliability in unbalanced medical data sets. Table 1 shows the Comparative Analysis of Selected Imbalanced Classification Studies.

Table 1. Comparative Analysis of Selected Imbalanced Classification Studies

| Ref. No. | Title                                                           | Authors & Year                         | Key Findings                                                                                                                  | Research Gaps                                                                                                      |
|----------|-----------------------------------------------------------------|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| [1]      | Respiratory sound classification using hybrid LSTM-KAN          | K.V. Nithinkumar and R. Anand (2026)   | Hybrid LSTM-KAN improves classification accuracy for imbalanced respiratory datasets and enhances feature learning stability. | Limited real-world multi-center validation; scalability and computational complexity not extensively analyzed.     |
| [2]      | Explainable AI-based stress detection using TabNet              | S.J.J. Janifer Jabin Jui et al. (2026) | TabNet with physiological signals provides interpretable stress detection and improved minority-class sensitivity.            | Generalization across diverse demographic groups remains unexplored; robustness to noisy signals needs validation. |
| [3]      | Financial statement classification using GAN-based augmentation | S. Gangopadhyay and U. Bharambe (2026) | GAN-based synthetic data improves minority-class representation and boosts classification precision.                          | Risk of synthetic data bias; lack of evaluation on large-scale real-world financial datasets.                      |
| [4]      | Multi-class skin cancer                                         | A.V. Dahat et al. (2025)               | Stochastic gradient                                                                                                           | Limited dataset diversity;                                                                                         |

|     |                                                                |                            |                                                                                                    |                                                                                                          |
|-----|----------------------------------------------------------------|----------------------------|----------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
|     | detection using SGD augmentation                               |                            | augmentation combined with activation mapping enhances multi-class skin lesion detection accuracy. | explainability evaluation metrics not deeply investigated.                                               |
| [5] | MRI brain tumor classification using adaptive GAN augmentation | A. Mahadevan et al. (2025) | Adaptive GAN augmentation improves tumor classification performance and model explainability.      | Requires validation on heterogeneous MRI scanners; computational overhead of GAN training not optimized. |

In addition to the domain of medical imaging, augmentation and imbalance-handling methods are also being used to text analytics, big data and tabular learning tasks. Sentiment models based on transformers can be used to improve the abusive Tamil comment classification on the social platform [6], and sentence transformers with machine learning can be used to solve the multi-class research article classification under skewed distributions [12]. Ensemble systems in semi-supervised mode minimize effects of imbalance in massive datasets [9], and SMOTE augmentation advances lower back pain detection [14]. When synthetic tabular data generation algorithms are used, overlap-class modeling can surprisingly achieve a higher result in the achievability of minority-class separability [15]. The relevance of transfer learning to heterogeneous conditions of data can also be emphasized by the variability of the data within the diabetic retinopathy classification [11]. In the meantime, SeisAug is an application generalized to augmentation in domain-specific applications in geoscience [17]. Collectively, these works point to a paradigm shift in methodology between the mere resampling to the domain-sensitive model of synthetic data. Imbalance-aware detection systems are important in the process of ensuring operational integrity in cybersecurity and industrial applications. Boundary-adaptive oversampling complements minority classes detection, enriching their boundaries [19], whereas feature-selective IoT intrusion detection systems (EFS-IDS) are useful in detecting anomalies in traffic in highly skewed distributions [20]. The comparative studies of the imbalance-handling methods on CNN-based solar photovoltaic fault diagnoses indicate that the augmentation and cost sensitive learning can greatly increase the detection accuracy [10]. Sparse regularised autoencoders enhance prediction of gene mutations in the radiomics of lung cancer through learning compact, discriminative representations [18], which increases the significance of the representation learning in low-data settings. In all studies [1]–[21], one tendency is present: hybrid deep learning, GAN-based augmenting, transformers based modeling, and adaptive oversampling develop the robustness, explainability, and generalization in imbalanced classification problems in a specific move towards more intelligent data-driven systems.

3 Methodology

The process follows a well-defined pipeline to effectively address the problem of class imbalance using Generative AI to augment the dataset. First, the dataset goes

through a preprocessing step to remove unwanted values, normalize the values, encode the features, and explore the statistics to determine the degree of class imbalance. Imbalance degree measurement includes class distribution metrics and the imbalance ratio (IR). Next, the dataset is split into training, validation, and test sets to evaluate the performance of the classifiers. Then, the minority class and majority class are identified, followed by a baseline evaluation of the classifiers' performance using conventional machine learning classifiers.

### 3.1 Imbalance Ratio

$$IR = N_{maj} / N_{min} \quad (1)$$

where  $N_{maj}$  and  $N_{min}$  denote majority and minority class samples.

### 3.2 GAN Objective

$$\min_G \max_D V(D, G) = E_x[\log D(x)] + E_z[\log(1 - D(G(z)))] \quad (2)$$

where  $G$  is the generator,  $D$  is the discriminator,  $x$  is real data, and  $z$  is latent noise.

### 3.3 VAE Loss

$$L_{VAE} = E_{q(z|x)}[\log p(x|z)] - D_{KL}(q(z|x) \parallel p(z)) \quad (3)$$

where  $q(z|x)$  is the encoder distribution and  $D_{KL}$  is the KL divergence.

### 3.4 Weighted Classification Loss

$$L = - \sum_{i=1}^C w_i y_i \log(\hat{y}_i) \quad (4)$$

where  $w_i = N / (C \cdot N_i)$  balances minority classes.

#### Algorithm 1. Generative Synthetic Data Augmentation

- 1: Input dataset  $D$
- 2: Compute IR
- 3: if  $IR > \tau$  then
  - 4: Train GAN/VAE on minority data
  - 5: Generate and validate synthetic samples
  - 6: Augment dataset
- 7: end if
- 8: Train classifier using balanced loss
- 9: Output optimized model




Fig. 1. Proposed Methodology.

Algorithm 1 shows the Generative Synthetic Data Augmentation. In the second step, deep generative models are developed to effectively capture the underlying distribution of the minority class. For this, Generative Adversarial Networks (GAN) and Variational Autoencoders (VAE) are used. GAN consists of a generator network that generates synthetic data and a discriminator network that learns to distinguish between real and synthetic data. During training, the discriminator tries to classify the real and synthetic data, which acts as a constraint to the generator to generate synthetic data indistinguishable from real data. VAE, on the other hand, maps the input to a latent space using the encoder network and decodes the input using the decoder network. The third step focuses on validating the synthetic data, which also includes the incorporation of synthetic data generation into the overall workflow. In this step, the synthetic data generated is validated for realism and diversity by examining the statistical similarity, the alignment of the feature distribution, and the overall visualization of the data. This synthetic data that has been validated for quality and diversity is then merged with the original data set, which has been balanced. This new balanced data set, which includes the synthetic data, is then used for re-training the machine learning as well as the deep learning classifiers under the same conditions. In the last step, the classifiers are tested for performance, with the evaluation metrics for the imbalanced data set comprising precision, recall, F1-score,

balanced accuracy, MCC, and AUC-ROC. In addition, the results obtained can also be compared with traditional methods such as random oversampling, undersampling, and SMOTE. Statistical tests can also be conducted for validating the results obtained. This overall process can be implemented in a Python-based environment, which would be useful for the overall applicability of the proposed approach for generative data augmentation.

4 Results and Evaluations

In the imbalanced scenario, the minority class constitutes only 10% of the data, i.e., 1/9. In this case, the baseline model without any form of data augmentation achieved an accuracy of 91.2%. However, the model struggled with the minority class, obtaining a recall of only 62.4%, an F1-score of 0.68, and a balanced accuracy of 71.5%. When traditional resampling methods, namely Random Oversampling and SMOTE, were applied, the minority class obtained a higher recall, i.e., 74.8% and 78.3%, with corresponding F1-scores of 0.76 and 0.79. However, some signs of overfitting were also noticed, as the model's performance varied by approximately  $\pm 3.5\%$ . Table 2 shows the Performance Comparison of Different Imbalance Handling Techniques.

Table 2. Performance Comparison of Different Imbalance Handling Techniques

| Method                 | Recall (%) | Precision (%) | F1-Score | Balanced Acc. (%) | AUC-ROC | MCC  |
|------------------------|------------|---------------|----------|-------------------|---------|------|
| Baseline (No Aug.)     | 62.4       | 74.1          | 0.68     | 71.5              | 0.82    | 0.59 |
| Random Oversampling    | 74.8       | 78.6          | 0.76     | 79.2              | 0.87    | 0.70 |
| SMOTE                  | 78.3       | 80.4          | 0.79     | 82.5              | 0.89    | 0.74 |
| VAE-Based Augmentation | 84.7       | 83.2          | 0.84     | 86.8              | 0.91    | 0.78 |
| GAN-Based Augmentation | 88.6       | 85.9          | 0.87     | 89.3              | 0.93    | 0.81 |
| Hybrid GAN-VAE Model   | 91.4       | 87.5          | 0.89     | 91.1              | 0.95    | 0.83 |

When the Generative AI-based data augmentation framework, which utilized GANs, was integrated, the model's performance improved substantially. By artificially inflating the minority class from 10% to 45%, the model achieved a much higher minority class recall of 88.6%, precision of 85.9%, and F1-score of 0.87.




Fig. 2. F1-Score Comparison Across Methods.

In addition, the balanced accuracy increased to 89.3%, while the AUC-ROC increased from 0.82 (baseline) to 0.93. The VAE-based data augmentation also showed a good improvement, with the model obtaining a minority class recall of 84.7%, precision of 83.2%, F1-score of 0.84, and balanced accuracy of 86.8%.




Fig. 3. Balanced Accuracy Distribution Across Methods.

However, the hybrid model consisting of GAN and VAE outperformed the other models, with the model obtaining a minority class recall of 91.4%, F1-score of 0.89, balanced accuracy of 91.1%, and an increased AUC-ROC of 0.95. Cross-validation of the proposed method on 5-fold data showed that the proposed method was robust as the variation of the proposed method was reduced to less than  $\pm 1.2\%$ . Matthews Correlation Coefficient was improved from 0.59 to 0.83 using the proposed method compared to the traditional method. The proposed method was further validated by performing a statistical test using a paired t-test, which showed a p-value of 0.004

(<0.01). The proposed method is validated as a powerful generative AI-driven synthetic data augmentation method for significantly enhancing minority class recognition, reducing classification bias, and improving the generality of the classifier.

## 5 Challenges and Limitations

Despite the robust promise of performance improvements, the Generative AI-based Synthetic Augmentation Framework still has to contend with a set of challenges. The process of training a Generative AI, like a GAN, is computationally expensive and requires a lot of time, memory, and computational power, particularly when working with large data sets. The challenges include mode collapse, instabilities in adversarial learning, and convergence difficulties, which might compromise the quality and variety of the generated samples. The VAE has its own challenges too, which often result in generated samples that lack sufficient texture and realism, particularly because they might be too smooth and lack the complexity that is often a result of a constraint in the latent space. Adjusting the hyperparameters, which include learning rates, dimensions, and depths, is a further complexity that might result in inferior synthetic data samples. The authenticity and representativeness of the generated samples remain a major limitation for the Generative AI-based Synthetic Augmentation Framework. Despite the use of statistical measures and data visualization, it remains a problem to ensure that the generated data samples represent the characteristics and diversity of the minority classes without introducing noise and biases into the data. There exists a possibility that the generated data might, in fact, amplify the biases that might have existed in the original data. The use of artificially generated data might be further constrained by ethical and regulatory implications, particularly in fields like healthcare and finance. The problem might be further complicated when working with large data sets and when working with data from different domains.

## 6 Future Outcomes

Future research directions will continue to increase the robustness and scalability of the Generative AI-based synthetic data augmentation. This could involve exploring more advanced generative models, such as Conditional GANs, Wasserstein GANs, and even diffusion models, to increase the robustness and diversity of the data. The incorporation of attention mechanisms and transformers could be beneficial for learning features of the minority class in high-dimensional data, including medical images, cybersecurity data, and financial data. Furthermore, hyperparameter optimization using meta-learning and Automated Machine Learning can be beneficial for improving the ease of use and robustness of the data augmentation process. Another promising research direction is to combine data augmentation with Federated Learning and Privacy-Preserving AI. This can be beneficial for secure data generation in distributed environments, especially in medical, IoT, and autonomous vehicle

applications, where data sharing is heavily constrained. Furthermore, Explainable AI can be beneficial for understanding the impact of synthetic data on decision boundaries and classification. In the near future, synthetic data can be beneficial for real-time data processing pipelines, especially for correcting class imbalance and tuning model performance in real-time data streams.

## 7 Conclusion

This research demonstrates that the use of Generative AI for data generation can indeed prove to be an effective solution for addressing the issue of class imbalance in supervised learning scenarios. With the ability to tap into the power of deep learning models such as GANs and VAEs, the effectiveness of the minority class representation is significantly improved by reducing bias towards the majority class and increasing other key performance metrics such as recall, F1-score, balanced accuracy, MCC, and AUC-ROC. Even though there are certain challenges associated with the computational cost of generative models and the validation of synthetic data, the overall results demonstrate significant promise for the use of Generative AI techniques within real-world scenarios such as those within the fields of healthcare, cybersecurity, finance, and intelligent systems. Overall, the inclusion of Generative AI within class imbalance learning scenarios is a significant step towards fairer, more reliable, and better-performing machine learning models.

## References

1. K. V. Nithinkumar and R. Anand, "Investigation into respiratory sound classification for an imbalanced data set using hybrid LSTM-KAN architectures," *Comput. Methods Programs Biomed. Update*, vol. 9, Art. no. 100227, 2026, doi: 10.1016/j.cmpbup.2025.100227.
2. S. J. J. Janifer Jabin Jui, R. C. Deo, U. R. Acharya, P. D. Barua, J. Soar, and A. Devi, "Automated stress detection with explainable-AI transformer TabNet technique and physiological signals," *Biomed. Signal Process. Control*, vol. 113, Art. no. 109208, 2026, doi: 10.1016/j.bspc.2025.109208.
3. S. Gangopadhyay and U. Bharambe, "Enhanced financial statements classification by synthetic data augmentation using generative adversarial networks (GANs)," *Lecture Notes in Networks and Systems*, vol. 1536, pp. 427–443, 2026, doi: 10.1007/978-981-96-9239-2\_30.
4. A. V. Dahat, U. T. Kute, T. R. Mahore, A. A. Joshi, S. D. Pande, and U. Desai, "Detection of multi-class skin cancer using stochastic gradient descent augmentation model and activation mapping," *J. Innov. Image Process.*, vol. 7, no. 4, pp. 1415–1435, 2025, doi: 10.36548/jiip.2025.4.018.
5. A. Mahadevan, R. K. Reddy, U. Nadimpalli, M. Khaji, B. Nannuru, and A. Akkina, "Efficient and explainable MRI brain tumor classification via adaptive GAN-based data augmentation," *Array*, vol. 28, Art. no. 100609, 2025, doi: 10.1016/j.array.2025.100609.
6. M. Subramanian, V. E. Sathishkumar, P. S. Nandhini, and U. Moorthy, "Empowering sentiment analysis in social media: A comprehensive approach to enhance the

- classification of abusive Tamil comments using transformer models,” *J. Big Data*, vol. 12, no. 1, Art. no. 208, 2025, doi: 10.1186/s40537-025-01268-6.
7. M. Gowri Shankar, S. Karthikeyan, H. Rajaguru, S. V. Talawar, and R. S. Rajanna, “A holistic strategy of modified superpixel segmentation and randomized Adam hyperparameter tuning with deep learning approaches for the classification of breast cancer from BreakHis images,” *Int. J. Comput. Intell. Syst.*, vol. 18, no. 1, Art. no. 133, 2025, doi: 10.1007/s44196-025-00877-6.
  8. S. Chakraborty et al., “Generative adversarial network augmented data for improved heart sound abnormality detection,” *Comput. Biol. Med.*, vol. 195, Art. no. 110623, 2025, doi: 10.1016/j.combiomed.2025.110623.
  9. S. Sindhu and S. Veni, “A semi-supervised ensemble classification with data augmentation to reduce imbalanced class distribution in big data,” *SSRG Int. J. Electron. Commun. Eng.*, vol. 12, no. 7, pp. 1–12, 2025, doi: 10.14445/23488549/IJECE-V12I7P101.
  10. P. R. Sonawane et al., “Comparative analysis of methods used to solve class imbalance problem in dataset for CNN-based fault diagnosis of solar photovoltaic panels,” *Int. J. Thermofluids*, vol. 28, Art. no. 101303, 2025, doi: 10.1016/j.ijft.2025.101303.
  11. K. Patni, S. B. Yagnik, and P. K. Patel, “Exploring dataset variability in diabetic retinopathy classification using transfer learning approaches,” *J. Electron. Electromed. Eng. Med. Inform.*, vol. 7, no. 3, pp. 763–777, 2025, doi: 10.35882/jeeemi.v7i3.838.
  12. S. Gowhar et al., “Imbalanced multi-class research article classification using sentence transformers and machine learning algorithms,” *Proc. 8th Jt. Int. Conf. Data Sci. Manage. Data (CODS-COMAD 2024)*, pp. 309–310, 2025, doi: 10.1145/3703323.3703698.
  13. N. R. Desidi et al., “DCDNet: A deep learning framework for automated detection and localization of dental caries using oral imagery,” *Indones. J. Electr. Eng. Inform.*, vol. 13, no. 2, pp. 478–499, 2025, doi: 10.52549/ijeei.v13i2.6245.
  14. P. Praveen, M. S. Mallikarjunaswamy, and M. Mamadapur, “Automated detection of lower back pain using machine learning and SMOTE-based data augmentation,” *SSRG Int. J. Electron. Commun. Eng.*, vol. 12, no. 5, pp. 350–362, 2025, doi: 10.14445/23488549/IJECE-V12I5P129.
  15. A. D'souza, M. Swetha, and S. Sarawagi, “Synthetic tabular data generation for imbalanced classification: The surprising effectiveness of an overlap class,” *Proc. AAAI Conf. Artif. Intell.*, vol. 39, no. 15, pp. 16127–16134, 2025, doi: 10.1609/aaai.v39i15.33771.

16. D. Shamia et al., “Enhancing skin cancer classification with mixup data augmentation and EfficientNet,” *J. Electron. Electromed. Eng. Med. Inform.*, vol. 7, no. 2, pp. 557–566, 2025, doi: 10.35882/jeeemi.v7i2.703.
17. D. Pragnath et al., “SeisAug: A data augmentation python toolkit,” *Appl. Comput. Geosci.*, vol. 25, Art. no. 100232, 2025, doi: 10.1016/j.acags.2025.100232.
18. M. A. Munir et al., “Enhancing gene mutation prediction with sparse regularized autoencoders in lung cancer radiomics analysis,” *IEEE Access*, vol. 13, pp. 7407–7425, 2025, doi: 10.1109/ACCESS.2024.3523330.
19. R. Kaur and N. Gupta, “A novel boundary adaptive oversampling approach for intrusion detection,” *Indones. J. Electr. Eng. Comput. Sci.*, vol. 37, no. 1, pp. 518–529, 2025, doi: 10.11591/ijeeecs.v37.i1.pp518-529.
20. S. Gopikrishnan et al., “EFS-IDS: An enhanced feature-selective intrusion detection system for imbalanced IoT traffic data,” *IEEE Open J. Commun. Soc.*, vol. 6, pp. 9673–9695, 2025, doi: 10.1109/OJCOMS.2025.3630471.
21. R. Mahakud et al., “A hybrid VGGNet–vision transformer approach for leaf disease classification using PGGAN-augmentation,” *Int. J. Appl. Math.*, vol. 38, no. 4S, pp. 683–705, 2025, doi: 10.12732/ijam.v38i4s.261.

**Open Access** This chapter is licensed under the terms of the Creative Commons Attribution-NonCommercial 4.0 International License (<http://creativecommons.org/licenses/by-nc/4.0/>), which permits any noncommercial use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license and indicate if changes were made.

The images or other third party material in this chapter are included in the chapter's Creative Commons license, unless indicated otherwise in a credit line to the material. If material is not included in the chapter's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder.

