

Restoration Technology Research Progress of Mercury Polluted Farmland

Liu Zhijie

Center for Environmental Education &
Communications of Ministry of Environmental
Protection, Beijing, China
E-mail: thulzj@gmail.com

Li Ke

Engineering and Technology Centre of Lake,
Dongtinghu Lake Ecological Observation and Research
Station (DEORS), Research Centre of Lake
Environment, State Environmental Protection Key
Laboratory for Lake Pollution Control, State Key
Laboratory of Environmental Criteria and Risk
Assessment, Chinese Research Academy of
Environmental Sciences, Beijing 100012, China
E-mail: likerx1989@126.com

Xu Zhe

Patent Examination Cooperation Center of the Patent
Office, SIPO, Beijing, China
E-mail: 95847948@qq.com

Li Jianchao

Hunan Provincial Environmental Monitoring Center
Changsha, Hunan, China
E-mail: 315945774@qq.com

Lu Shaoyong*

Engineering and Technology Centre of Lake, Dongtinghu Lake Ecological Observation and Research Station (DEORS),
Research Centre of Lake Environment, State Environmental Protection Key Laboratory for Lake Pollution Control, State
Key Laboratory of Environmental Criteria and Risk Assessment, Chinese Research Academy of Environmental Sciences,
Beijing 100012, China, Corresponding Author
E-mail: lushy2000@163.com

Abstract—Soil is an important part of the environment, which is the precious renewable resources. Soil heavy metal pollution is becoming more and more serious, which affects the normal function of soil, causes pollution of food chain, threats to human health and environmental quality. Mercury as one of the persistent toxic pollutants, is also one of the precedence-controlled pollutants, soil mercury pollution problem has aroused high attention of the world. In our country, mercury discharge of about 1.9×10^8 kg/a into environments, covering 3.2×10^4 ha contaminated farmland, mercury as a kind of toxic heavy metals is non-necessary for human, posing a great risk to human health. Considering the circumstances of mercury pollution and the remediation demands, six kinds of commonly applied techniques were developed in the following aspects of working principles, researching progress, studying cases, advantages or disadvantages, and application scopes, and so on, supplying the technology support for the remediation plan of the mercury contaminated farmlands.

Keywords-Mercury Pollution;Farmland Soil;Remediation Technology;harm;application

I. INTRODUCTION

Since the last century, accidents of mercury pollution occurred frequently, such as Japan's Minamata Bay, Kumamoto Minamata disease event in 1956, event of four American children poisoned by mercury-fed pork, methyl-mercury dressing food poisoning event in Iraq in 1972. All these events have brought human beings and ecological environment great disaster^[1, 2].

Mercury is a potential neurotoxin heavy metal element^[3], UNEP, WHO, FAO and other international organizations list mercury as one of the priority control pollutants due to its persistence in the environment and bioaccumulation characteristics. Mercury pollution in soil mainly derive from the exploitation of gold mine and copper zinc ore, chloric alkali industry, wet deposition (dissolved mercury, Hg^{2+}) and dry deposition (particulate mercury, Hg^0) of atmospheric mercury generated by burning coal^[4-6]. In addition, sewage irrigation and soil improved by city sludge can also contribute to the increase of mercury and methyl-mercury concentrations in soil^[7]. Once mercury enters the soil, 95% of it can be fixed by soil or adsorption^[8], and it is difficult to be transformed or degraded^[9], therefore, the perniciousness of mercury in soils is cryptic, hysteretic and long-term, besides, it can harm human health by crops absorption and beneficitation of food chain transfer^[10, 11]. Thus, farmland soil pollution prevention has become the focus of many scholars both at home and abroad^[4, 12-14].

According to the study, soil in many domestic and foreign areas have been polluted to varying degrees by mercury^[5]. Every year in our country, the content of mercury invaded in the environment is about 1.9×10^8 kg, which leads to 3.2×10^4 ha of mercury-polluted cultivated land^[15]. The mercury pollution status in Songhua River basin of Jilin Province and Guizhou Wanshan area is serious^[16], human health survey suggests that mean content of mercury in Songhua River fishermen's hair in 1975 is 17.50 $\mu\text{g/g}$, in 1990 is 3.82 $\mu\text{g/g}$ and in 2000 is 2.15 $\mu\text{g/g}$,

though there is a downward trend, it is still higher than the 1mg/kg limit value enacted by the America Environmental Protection Bureau^[17]. Mean content of mercury in residents' hair in Guizhou Wanshan mercury mining area is 837 $\mu\text{g/g}$ ^[18], which far exceed the standard. The mercury content of soil in six sewage irrigation area in the eastern suburbs, western suburbs and northern suburbs of Xi'an with about 200 km² range is between 0.52 mg/kg and 0.90 mg/kg^[19]. Soil mercury concentration of sewage irrigation area in Huaiyin has exceeded one times more than mercury concentration in soil clean irrigation area, also exceed the limit value of second ambient soil quality standards (GB15618-1995)^[20].

There are mainly two ways to harness mercury pollution in soil. One is to change the mercury speciation in soil, transfer it from the active state to stable state, and reduce its bioavailability and migration activity^[21], the other is to reduce Hg content in soil by some measures^[22]. At present, there are several technologies frequently-used at home and abroad in remediation of soil contaminated with mercury, such as turning over the soil, soil method, heat treatment method, electric repair method, leaching method, stabilization and solidification method, bioremediation.

II. PHYSICAL REMEDIATION TECHNOLOGY

A. Soil aeration, soil replacement

Soil aeration is to disperse pollutants gathering in the surface soil into the deep. Soil replacement is to remove contaminated soil and cover uncontaminated soil, or to directly mix the contaminated soil and uncontaminated soil, with the aim of pollutants diluting. The two methods can be simply operated, but its workload is large, have a great disturbance on soil structure, and mercury in soil has not been fundamentally removed, so it is not suitable for the situation of heavy pollution or lack of land resources.

B. Thermal treatment

Thermal treatment uses heat or hot steam to make the volatile or semi volatile pollutants in the polluted soil into gas, centralized recovered or disposed^[23]. Mercury in soil mainly exists in the forms of elemental mercury and compounds such as HgS, HgO and HgCO₃, when the temperature gets 600 - 800°C, compounds will breakdown and release elemental mercury vapor, which will recover by off-gas treatment device^[24-25]. Thermal treatment is widely used in the remediation of mercury contaminated soil and has the advantages of simple operation, high treatment efficiency, the main process is shown in Fig .1.




Figure 1. Model of a Thermal Desorption or Retort System (From References [24-25])

Because of the large energy consumption, the high investment and operation costs of thermal treatment, and the truth that more than 500°C will cause the loss of soil nutrients, destroy the physicochemical properties of soil and soil structure, in recent years, low-temperature pyrolysis technology has been developed and applied. Zhang Qian^[26] treated the typical mercury contaminated soil of Wanshan Guizhou in the low-temperature of 370°C. The mercury in soil can be reduced into 10 mg/kg, treatment rate of 95.73%, and residual mercury in treated soil is mainly in slag state mercury. Qiu Rong^[8] researched the mercury contaminated farmland soil of Qingzhen Guizhou in low-temperature pyrolysis technology, showed that under 350°C, treatment rate could be more than 90%^[27]. Under the temperature of 300°C, the mercury contaminated soil around a waste factory of chlor alkali production in Qinghai, with the residence time of 60 min, mercury concentration is reduced to 10 mg/kg, the treatment rate is nearly 90%^[28]. Comuzzi disposed mercury contaminated sediment by co-induction using tetrabutylammonium chloride and thermal desorption, treatment rate increased from 24% to 60%^[29].

C. Vitrification


Vitrification uses hot heat source such as plasma and electric current, to melt contaminated soil at 1600 - 2000°C, contaminants are pyrolysed or vaporized, cooled melting will form corpora vitreum. It wraps contaminants and reduces the migration of contaminants. Once in treatment with mercury contaminated soil by vitrification technology in the US state of Michigan, the initial concentration of mercury is about 40 g/kg, after the treatment, available mercury concentration is less than 0.23 g/L^[30]. This technology can be operated via mobile devices in the field, but costs much.

III. CHEMICAL REMEDIATION TECHNOLOGY

A. Electrokinetic remediation

Electrokinetic remediation is the technology of inserting electrodes on both ends of the contaminated soil. Under the low voltage direct current field, the pollutants are transported into the electrode chamber, and finally collected through engineering methods, the main electrode reactions are as follows (E_0 is standard electrode potential)^[31]:

Anodic reaction:



Cathodic reaction:



This technology was first developed by the United States to purify contaminated soil in situ^[32], then gradually developed to strengthen electrokinetic remediation technologies, including electro dialysis method, complexing method, acid-base neutralization, cation-selective membrane method, surfactant method, oxidation-reduction method, EK-conjunction with biological and LasagnaTM method. Zheng Shenshen adopted the method of cathode electric supplemented by cation exchange membrane and KI + I₂ solution oxidation complex method to remediate mercury contamination typical paddy soil in Guizhou and the Hg removal efficiency can reach 68.6%^[33]. Reddy made the removal efficiency of mercury in the soil increase to 97% by adding 0.1 mol/L KI to kaolin^[34]. Cox added I₂/KI lixiviant in cathode and made the insoluble Hg into Hgl₄ complex anion, so that the mercury removal efficiency was as high as 99%^[35]. Electrokinetic remediation technology is suitable for low permeability soil such as clay, silt soil. This method has high removal efficiency and has no effect on the soil fertility, but the repair cost is high and electrolysis will cause changes in soil pH, repair mechanisms and reaction conditions need further research as well.

B. Soil leaching method

Soil leaching method is mainly used to deal with pollutants physically or chemically adsorbed on soil

particles. Eluent transfers the inorganic or organic pollutants from the soil solid phase to the liquid phase, then further treatment of the eluent contained pollutants is taken. Soil leaching removes pollutants in two ways: one is using eluent to dissolve contaminants in the liquid phase, adsorption phase and gas phase; another is using water to wash contaminants in soil pore or adsorbed on soil. The former is controlled by pollutant solubility and Henry's law constant, the latter depends on the pressure gradient, soil flushing water viscosity and the concentration of pollutants^[36]. The key of Mercury polluted soil leaching technology is to select eluent that both can better absorb mercury, and does not destroy the physical and chemical properties of soil. Some studies found that iodide, EDTA, thiosulfate compounds have good leaching effect^[37]. Lin Kai found that in severely mercury polluted soil, the mercury removal effect of eluent is NaOH solution > emulsifier > EDTA > DTPA > tartaric acid > phosphoric acid > glacial acetic acid > hydrochloric acid > nitric acid > citric acid > the agricultural irrigation water > CaCl₂ solution > precipitation water > deionized water, and the mercury removal rate in soil is from 6.5% to 37.5%^[38]. Chen Zongying^[39] found that Na₂S₂O₃ solution can efficiently remove the mercury in soil whose initial concentration is 108.76 mg/kg, removal rate is 65.32%. Ray^[40] used H₂O₂, Na₂S₂O₃, Na₂S to joint repair mercury polluted soil, whose initial concentration is 2100 mg/kg, terminative concentration is 270 mg/kg, mercury removal rate is 87%.

Since the United States GE Wiring Devices used KI solution as eluent to repair the mercury polluted places in 1992, large-scale heavy metal polluted soil leaching projects have been carrying out one after another. Kuhlman^[41] summarized ectopic soil leaching process, whose details are shown in Fig .2.




Figure 2. The flow diagram of soil ex-situ washing

Chemical leaching technology can remove heavy metals from the soil efficiently and thoroughly. It is suitable for repairing small area of soil which is polluted by heavy metal. It also can serve as a pretreatment technology, then combined with other methods to repair the contaminated soil polluted by heavy metal^[42]. But the cost of chemical leaching technology is too high, and the use of drench lotion will reduce soil biological activity, so the application of chemical leaching technology is still in its infancy in our country.

C. Solidification/stabilization

The theory of solidification/stabilization technology is as following: adding reagent into the soil, pollutant reacting with reagent for physic-chemical reaction, turning it into fixed mercury, so as to reduce the mobility of mercury in soil. Cement, ash and many other substances are the commonly used physical curing agents. Cement is economic and the most commonly used, it converted the mercury in soil to mercuric oxide precipitation, and then fixed it in the concrete block^[43]. Commonly used materials for stabilization are s-based compound, zeolite, lime, calcium carbonate, phosphate, silicate, etc. Lime or calcium carbonate was mainly used to improve the pH value of soil, and made Hg and other elements in soil form precipitation of combination state salt of hydroxide or carbonate^[44]. Zeolite can decrease the effectiveness of the heavy metals in soil through ion exchange adsorption and specific adsorption^[27].

Chao^[45] used Na₂S and cement as curing agent to dispose of mercury polluted soil from a chemical company.

When the pH value was 8, the mercury concentration in the leaching liquid of curing block was lower than 1 ng/L and achieved the goal of innocent treatment of mercury polluted soil. Wu^[46] optimized the ratio of stabilizer and curing agent to repair mercury polluted soil at a chemical enterprise in Yunnan, and improved the economic feasibility of the restoration work, made a significant reduction of mercury concentration in the leaching liquid. Wang^[47] used the technology of adding fly ash to dropped mercury concentration in soil significantly.

Using solidification/stabilization technology to repair mercury polluted soil had good effect and low cost, but mercury is still exist in the soil, and the treated soil loses agricultural productivity and other functions.

IV. BIOREMEDIATION TECHNIQUE

A. Phytoremediation

Phytoremediation is to use the extraction effect, volatile effect and curing effect of plants to reduce the content of mercury in soil^[48].

The key of phytovolatilization technology is to embed mercury invertase genes into the plant bodies, then the plant can compound mercury invertase to transform combining state of mercury into zero-valent mercury when the combining state of mercury is absorbed from the soil into the plant, then the zero-valent mercury can be released by leaf transpiration. Researchers have implanted mercury reductase genes and organic lyase genes into many wetland plants such as typha, rice, rice straw and others. Meagher^[49] obtained transgenic plants-arabidopsis whose

tolerance ability of organic mercury increased 50 times. He^[50] embedded the MerA genes of bacteria into tobacco, which made it can normally grow in HgCl₂ medium within 50 μM ~ 350 μM.

Perennial evergreen plants, resistant to high concentrations of heavy metals and root developed, could reduce the activity of heavy metals through root decomposition, precipitation, chelation, redox and so on, thus reduce the metal leaching into groundwater or the possibility of further environmental pollution through the air spread, which is referred to as plant curing^[51]. The study indicates that the mercury enrichment capacity could reach 10 mg/kg by silver birch, while the maximum mercury absorption accumulation of Canada Populus was about 7 mg/kg^[52]. Root is the main tissue part for mercury curing, the mercury content in the leaves of lobular boxwood accounting for 8.6% of that in the root soil^[53]. Only 0.45% ~ 0.65% of absorbing mercury by willow root cell wall were transferred to the overground part of plant^[54]. Compared with rape, wheat and pea, willow had not been found releasing mercury into the atmosphere^[55]. Rice straw had stronger resistance to mercury^[56] by converting organic mercury to inorganic mercury, which showed well potentiality of mercury-contaminated soil repairing. Humic acid could increase the residual mercury quantity in soil, and reduce the plant availability of mercury, thus effectively restraining the mercury accumulation in leaf^[57-58].

Heavy metal hyperaccumulation plants absorb heavy metals in soil, transfer them to the overground parts to storage, then harvest to removal, which is called as plant extract. Mercury-hyperaccumulation plants have not been found. By artificial induction and adding the chelating agents such as Na₂S₂O₃, KI, NH₄SCN, EDTA and (NH₄)₂S₂O₃^[59], the mercury extraction ability of plant was improved. Plant species is an important factor affecting the absorption of heavy metals. Huckabee^[60] pointed out that the mercury enrichment capability of herbaceous plants was obviously higher than that of woody. Liu^[61] found that the total mercury content in wetland plant was higher than that in upland crops, and the total mercury content in typical plants were as following: moss > algae > carex > grass > bush. Huang Hui^[62] discovered that the addition of Na₂S₂O₃ could significantly promote the absorption of various forms of mercury in calendula and mustard, while the mercury enrichment in root was stronger than that in stem leaf part. Wang J also found that after adding thiosulfate in the soil, the content of effective state of mercury in soil was significantly increased, improving the phytoremediation efficiency of mercury-polluted soil by Indian mustard^[63]. The mercury contents in the leaf, stem and root of tuber fern under slightly acidic conditions were higher than those under acidic or alkaline conditions^[64]. Wet earth pot method research showed that the amount of mercury enrichment of different tissues and organs in bamboo reed were in order of root > stem > leaf^[65].

Phytoremediation technology is of low cost and simple operation, which is suitable for a large area governance of mercury-polluted soil. However, the governance cycle is too long, during which the mercury evaporating into the atmosphere will cause certain influence to human health, and plants for heavy metals absorbing should be harvested and harmless timely.

B. Bioremediation

The use of microbial activity can adsorb or transform heavy metal affinity in the soil, increase stable-state metal content and thereby reduce the risk of being absorbed by organisms^[66-67]. Recent studies have found that a mercury-resistant microbe with mer operon can effectively control mercury pollution in soil and water^[68-69], and the evaporation rate of mercury in the soil was proportional to the number of microbes^[70]. Spangler^[71] inoculated four pseudomonades in a closed volumetric flask containing 50 ml culture media and 25 μg methylmercury bromides. After culturing for 5 days, methylmercury reduced by 50 %, and the upper part of the air in the flask generated methane and mercury vapor. In the experiment, Shariat^[72] isolated 40 kinds of bacteria from soil, sediment and sewage treatment substance, among which 21 kinds of bacteria can achieve methylmercury demethylation. In addition, bacterial degradation range for methylmercury under aerobic conditions can be from 20% to 84% and desulfovibrio de-sulfuricans decreased 32% of methylmercury under anaerobic conditions. Japan developed a bioremediation technology that can collect bacteria rich in mercury and to remove mercury by the method of evaporation, activated carbon adsorption^[77]. Yang Juhua^[73] selected a highly mercury-resistant strain of pseudomonas putida, and after 48 hours, the reduction efficiency of 5 ~ 50 mg/L Hg²⁺ is from 94.3 % to 82.8%. Li Mengjie^[74] took use of schizophyllum GGHN08-116 strain and cottonseed hull and corn stalk as substrate for solid-state fermentation to restore soil contaminated by mercury, lead and chromium so that the contents of these exchangeable elements can be decreased, while mercury and lead in carrots undetected.

Although the bioremediation is low in cost, high in efficiency and has little impact on environment, the treatment effect is limited by the type of contaminants and the restoration time lasts long.

ACKNOWLEDGMENT

The authors are grateful to acknowledge the financial support of to the NSF of China (41373027), the National Major Science and Technology Project for Water pollution Control and Management(No.2012ZX07105-002,2013ZX07101-014) and (2012-YSKY-14).

REFERENCES

- [1] YANG Hai,LI Ping, QIU Guang-le. Mercury pollution in mercury mining areas throughout the world:an overview[J].Earth and Environment, 2009,37(1):80-85.
- [2] QIN Dong-li,JIANG Qiu-li, FU You-sheng.Global review and analysis of mercury pollution[J].Environmental Protection Science, 2009,35(4):75-78.
- [3] ZAGURY G J,NEEULITA C M,BASTIEN C,et al. Mercury fractionation,bioavailability and ecotoxicity in highly contaminated soils from chlor-alkali plants[J].Environmental Toxicology and Chemistry,2006,25(4):1138-1147.
- [4] FANG Feng-man,WANG Qi-chao.A review on the studies on mercury pollution of soil[J].Soil and Environmental Sciences. 2000,9(4):326-329.
- [5] LIU Zhao-zhao,TANG Hao,WU Jian.Review of mercury-contaminated soil and the remediation techniques[J]. Environmental Engineering. 2013,31(5):80-84.
- [6] SCHROEDER W H,ANLAUF K G,BARRIE L A,et al.Arctic springtime depletion of mercury [J]. Nature,1998,394:331-332.

- [7] ANTHONY C. Methyl mercury contamination and emission to the atmosphere from soil amended with municipal sewage sludge[J]. *Journal of Environment Quality*, 1997, 26(6):1650-1655.
- [8] QIU Rong, ZHANG Jun-fang, DONG Ze-qin, et al. Low-temperature thermal desorption of farmland soil contaminated by mercury[J]. *Environmental Science & Technology*, 2014, 37(1): 48-52.
- [9] YANG Qin. Salt-assisted thermal desorption treatment technology of mercury-contaminated soils[J]. *Shan Xi: Northwest Sci-Tech University of Agriculture and Forestry*, 2013.
- [10] LI Ping, FENG Xin-bin, QIU Guang-le, et al. Mercury exposure in the population from Wuhan mercury mining area, Guizhou, China[J]. *Science of the Total Environment*, 2008, 395(2-3): 72-79.
- [11] XU You-ning, KE Hai-ling, LIU Duan-ping, et al. Environmental effect of mercury contamination of farmland soils in the Tongguan gold mining area, Shaanxi, China. *Geological Bulletin of China*[J]. *Geological Bulletin Of China*, 2006, 25 (11):1349-1353.
- [12] WANG Xin, ZHOU Qi-xing. Soil mercury pollution and remediation technique[J]. *Chinese Journal of Ecology*, 2002, 21(3): 43-46.
- [13] CUI De-jie, ZHANG Yu-long. Current situation of soil contamination by heavy metals and research advances on the remediation techniques [J]. *Chinese Journal of Soil Science*, 2004, 35(3): 366-370.
- [14] YANG Zhong-fang, ZHU Li, CHEN Yue-long, et al. *Modern environmental geochemistry* [M]. Beijing: Geological Publishing House, 1999, 381-382.
- [15] JIANG Da-meng, DENG Tian-long, LAI Dong-mei, et al. Phytoremediation of mercury contaminated soil: A review[J]. *Science and Technology Innovation Herald*, 2010, 1:126-128.
- [16] DING Zhen-hua, WANG Wen-hua, QU Li-ya, et al. Mercury pollution and its ecosystem effects in Wanshan mercury mine area, Guizhou [J]. *Environmental Science*, 2004, 25(2): 111-114.
- [17] XIN Wei-hong, HOU Tie-ning. Study on the methyl mercury pollution in Songhua river[J]. *Chinese Journal of Control of Endemic Diseases*, 2003, 18(2): 103-104.
- [18] LI Yu-feng, CHEN Chun-ying, XING Li, et al. Concentrations and XAFS speciation in situ of mercury in hair from populations in Wanshan mercury mine area, Guizhou Province[J]. *Nuclear Techniques*, 2004, 27(12): 899-903.
- [19] XIAO Yun-ying, LI Qing, ZHANG Rui-juan, et al. Impact of wastewater irrigation on crop mercury content[J]. *Environmental research and monitoring of Gansu*, 1997, 10(4):18-20.
- [20] ZHANG Shu-hai, SHEN Yiao-wen. Danger to soil by heavy metals pollution from polluted irrigation[J]. *The Administration and technique of environmental monitoring*, 2000, 12(2): 22-24.
- [21] LI Pei-jun, LIU Wan, SUN Tie-heng, et al. Remediation of contaminated soil: its present research situation and prospect[J]. *Chinese Journal of Ecology*, 2006, 25(12): 1544-1548.
- [22] ZHENG Shu-wen. Spatial distribution and pollution assessment of mercury in soil at a contaminated site [D]. Lan Zhou: Lan Zhou University, 2013.
- [23] MICHAEL V. Mercury clean up: the commercial application of its new mercury removal [J]. *Remediation*, 1995, 5(3):89-101.
- [24] USEPA. Treatment technologies for mercury in soil, waste and water [R]. EPA-542-R-07-003, 2007.
- [25] CHANG T C, YEN J H. On-site mercury-contaminated soils remediation by using thermal desorption technology [J]. *Journal Of Hazardous Materials*, 2006, 128(2-3): 208-217.
- [26] ZHANG Qian, XU Duan-ping, DONG Zeqin. Effects of temperature on mercury fractions in contaminated soil during the thermal desorption process[J]. *Research of Environmental Sciences*, 2012, 25(8): 870-874.
- [27] LAI Li. Remediation of mercury-contaminated soils by using low temperature thermal desorption in Guizhou Qingzhen [D]. Gui Zhou: Guizhou Normal University, 2008.
- [28] YANG Qin, WANG Xing-run, MENG Zhao-fu. Effect of thermal desorption treatment technology on mercury contaminated soils [J]. *Acta Agriculturae Boreali-Occidentalis Sinica*, 2013, 22(6):203-208.
- [29] COMUZZI C, LESA B, ANEGGI E, et al. Salt-assisted thermal desorption of mercury from contaminated dredging sludge[J]. *Journal of Hazardous Materials*, 2011, 193(15): 177-182.
- [30] KUNKEL A M, SEIBERT J J, ELLIOTT L J, et al. Remediation of elemental mercury using in situ thermal desorption (ISTD)[J]. *Environmental Science Technology*, 2006, 40(7):2384-2389.
- [31] MA Li, ZHANG Guo-qing, ZENG Cai-ming. Progress in the application of chemical enhancers in electrokinetic remediation process[J]. *Chemical Industry and Engineering Progress*, 2008, 27(1):38-44.
- [32] SAV H, CHRISTOPHER J. Integrated in situ soil remediation technology: The Lasagna Process[J]. *Environmental Science Technology*, 1995, 29(10):2528-2534.
- [33] ZHENG Shen-shen. Study on in-situ remediation of typical mercury contaminated soil from Guizhou province [D]. Shanghai: Shanghai Jiao Tong University, 2006.
- [34] REDDY K R, CHAPARRO C, SAICHEK R E. Removal of mercury from clayey soils using electrokinetics[J]. *Journal of Environment Science and Health, Part A Environmental Science*, 2003, 38(2):307-338.
- [35] Cox C D, Shoesmith M A, Ghosh M M. Electrokinetic remediation of mercury-contaminated soils using iodine/iodide lixiviant[J]. *Environmental Science Technology*, 1996, 30(6):1933-1938.
- [36] WU Jian, SHEN Gen-xiang, HUANG Shen-fa. A review on engineering remediation techniques for VOCs-contaminated soils [J]. *Chinese Journal of Soil Science*, 2005, 36(3):430-435.
- [37] SUBIRÉS-MUÑOZ J, GARCÍA-RUBIO A, VEREDA-ALONSO C, et al. Feasibility study of the use of different extractant agents in the remediation of a mercury contaminated soil from Almaden[J]. *Separation Science and Technology*, 2011, 79(2):151-156.
- [38] LIN Kai. Leaching characteristics and leaching restoration research of serious mercury contaminated soil - with an example of Qingzhen, Guizhou [D]. Guizhou University, 2011.
- [39] CHEN Zong-ying, ZHANG Huan-zhen. Research on extract remediation technology of mercury-contaminated soil[J]. *Earth Science Frontiers*, 2012, 19(6):230-235.
- [40] RAY A B, SELVAKUMAR A. Laboratory studies on the remediation of mercury contaminated soils[J]. *Remediation*, 2000, 10(4):49-56.
- [41] KUHLMAN M I, GREENFIELD T M. Simplified soil washing process for a variety of soils[J]. *Journal of Hazardous Materials*, 1999, 66(1-2):31-45.
- [42] PENG Li-jun, YANG Tao, LIU Yun-guo, et al. Chemical leaching remediation of soil contaminated by heavy metals and PAHs [J]. *Environmental Protection of Chemical Industry*, 2008, 28(5):418-423.
- [43] MCWHINNEY H G, COCKE D L, BALKE K. An investigation of mercury solidification and stabilization in Portland cement using X-ray photoelectron spectroscopy and energy dispersive spectroscopy[J]. *Cement and Concrete Research*, 1990, 20(1):79-91.
- [44] ZHU Xiao-cui, QING Chang-le, PI Guang-hao. Study on soil mercury fraction and their influencing factors[J]. *Acta Pedologica Sinica*, 1996, 33(1):94-100.
- [45] Chao Bo-yang, Zheng Shu-wen, Wang You-le. Cement solidification processing method of mercury contaminated soil[J]. *Gansu Science and Technology*, 2012, 28(23):33-34.
- [46] WU Xue-yong, ZHANG Tao. Application research in stabilization/solidification for the remediation of mercury contaminated soil [J]. *Environmental Science Survey*, 2014, 33(1):6-10.
- [47] WANG Dian-wu, LIU Guo-xin. Effect of combination of sludge with flyash on soil physical properties and accumulation of mercury [J]. *Journal Of Agricultural University Of Hebei*, 1994, 17: 269-274.
- [48] LIU Ping, CHOU Guang-le, SHANG Li-hai. Phytoremediation of mercury contaminated soil: A review [J]. *Chinese Journal of Ecology*, 2007, 26(6):933-937.
- [49] TERRY N, BANUELOS G S. *Phytoremediation of contaminated soil and water*[M]. Florida, USA: CRC Press Inc, 2000:201-219.
- [50] HE Y K, SUN J G, FENG X Z, et al. Differential mercury volatilization by tobacco organs expressing a modified bacterial merA gene [J]. *Cell Research*, 2001, 11(3):231-236.
- [51] XING Qian-guo, FAN Wei-bin, ZHANG Tai-ping. On phytoremediation of heavy metal contaminated soils [J]. *Ecologic Science*, 2003, 22 (3):275-279.

- [52] LIN Zhi-qing, HUANG Hui-yi. Study on tolerance of woody-plants to heavy metal pollutants in air[J]. Journal of Plant Ecology, 1989,9(4):315-319.
- [53] WANG Ji, ZHAO Ze-xue, WANG Xue-mei. The comparisons between *Buxus sinica* and *Nerium indicum* Mill on the absorbing to mercury in soil [J]. Journal of Guizhou Normal University(Natural Sciences), 2007,25(2):17-19.
- [54] GREGER M, WANG Y, NEUSCHUTZ C. Absence of Hg transpiration by shoot after Hg uptake by roots of six terrestrial plant species[J]. Environmental Pollution, 2005,134(2):201-208.
- [55] WANG Y, GREGER M. Clonal differences in mercury tolerance accumulation and distribution in willow[J]. Journal of Environment Quality, 2004,33(5):1779-1785.
- [56] TIAN Ji-lin, ZHU Hai-yan, YANG Yu-ai, et al. Organic mercury tolerance, adsorption and transformation in spartina plants[J]. Acta Photophysiological Sinica, 2004,30(5):577-582.
- [57] LI Jing, CHEN Hong, CHEN Yu-cheng, et al. Preliminary study on the chemical components of kudingcha in sichuan [J]. Journal of Sichuan Agricultural University, 2003,21(3):234-240.
- [58] LI Bo, QING Chang-le, WEI Shi-qiang. Effect study of humic acids on volatilization of Hg from soil in plant[J]. Chongqing Environmental Science, 2002,24(1):40-42.
- [59] WANG J, FENG X, ANDERSON C, et al. Remediation of mercury contaminated sites A review[J]. Journal of Hazardous materials, 2012,221-222(1):1-18.
- [60] HUCKABEE J W, DIAZ F S, JANZEN S A, et al. Distribution of mercury in vegetation at Almadén, Spain[J]. Environmental Pollution, 1983,30(3):211-224.
- [61] LIU Ru-hai, WANG Qi-chao, LV Xian-guo, et al. Distribution and stock of mercury in typical wetland plant in the Sanjiang Plain [J]. Chinese Journal of Applied Ecology, 2004,15(2):287-290.
- [62] HUANG Hui, CHEN Hong. Progress of phytoremediation on soil polluted by mercury, cadmium and chromium [J]. Chinese Agricultural Science Bulletin, 2010,26(24):326-329.
- [63] WANG Jian-xu, FENG Xin-bin, SAHNG Li-hai. Effects of ammonium thiosulphate amendment on phytoremediation of mercury polluted soil[J]. Chinese Journal of Ecology, 2010,29(10):1998-2002.
- [64] Pan Zhi-ming. Renal fern phytoremediation technology research of arsenic, mercury, lead, cadmium compound pollution soil[D]. Chengdu University of Technology, 2006.
- [65] HAN Zhi-ping, HU Xiao-bin, HU Zheng-hai. Phytoremediation of mercury and cadmium polluted wetland by *Arundo donax*[J]. Chinese Journal of Applied Ecology, 2005,16(5):945-950.
- [66] WU H Y, TING Y P. Metal extraction from municipal solid waste (MSW) incinerator fly ash Chemical leaching and fungal bioleaching[J]. Enzyme Microb Tech, 2006,38(6):839-847.
- [67] TENG Ying, HUANG Chang-yong. Ecological effect of heavy metals on soil microbes and research advances on the mechanisms of bioremediation[J]. Soil and Environmental Sciences, 2002,11(1):85-89.
- [68] ESSA A M, MACASKIE L E, BROWN N L. Mechanisms of mercury bioremediation[J]. Biochemical Society Transactions, 2002,30(4):672-674.
- [69] NASCIMENTO AM, CHART ONE-SOUZA F. Operonmer: bacterial resistance to mercury and potential for bioremediation of contaminated environments[J]. Genet Mol Res, 2003,2(1):92-101.
- [70] SEHOLTZ M T, VANHEYST B J, SCHROEDER W H. Modelling of mercury migrations from background soil[J]. Science of the Total Environment, 2003,304(1-3):185-207.
- [71] SPANGLER W J, SPIGARELLI J L, ROSE J M, et al. Degradation of methylmercury by bacteria isolated from environmental samples[J]. Applied and Environment Microbiology, 1973,25(4) : 488-493.
- [72] SHARIATM, ANDERSON A C, MASON J W. Screening of common bacteria capable of demethylation of methyl mercuric chloride[J]. B EnvironContamTox, 1979,21(1):255-261.
- [73] YANG Ju-hua, ZHAN Li-qin, CHEN Ling, et al. Study on the Isolation and Bio2characteristics of High Mercury resistant Bacteria[J]. Strait Journal of Preventive Medicine, 2006,12(1):5-7.
- [74] LI Meng-jie, WANG Cui-ling, LI Rong-chun. Microorganism remediation of Hg, Pb and Cr contaminated soil [J]. Chinese Journal of Environmental Engineering, 2013,7 (4):1568-1572.