











first reviewed some well-known approaches for statistical model selection and the advantage of using the MDL criterion. Then a one-dimensional example was used to illustrate the MDL criterion for multiple composite hypothesis testing and the performance limit of the ML-PDA for track initiation interpreted in terms of the sharpness of the hypothesis testing. Finally, We applied the MDL approach for the detection and initiation of tracks of incoming tactical ballistic missiles in the exo-atmospheric phase using a surface based electronically scanned array (ESA) radar. The targets were characterized by low SNR, which lead to low detection probability and high false alarm rate. A batch of radar scans were processed to detect the presence of up to two targets. The ML-PDA estimator was used to initiate the tracks assuming the target trajectories follow a deterministic state propagation. The approximate MDL criterion was used to determine the number of valid tracks in a surveillance region. The detector/estimator was shown to be efficient even at 4.4dB average SNR (within the beam, i.e., in a resolution cell).

## References

- [1] H. Chen, T. Kirubarajan, and Y. Bar-Shalom, “Multiple Low Observable Ballistic Missile Track Initiation Using an ESA Radar” , ESP Lab Tech Report, University of Connecticut, March 2001.
- [2] F. Daum, “A System Approach to Multiple Target Tracking”, in *Multitarget-Multisensor Tracking: Applications and Advances II*, Y. Bar-Shalom, Ed., 1992.
- [3] O. E. Drummond, “Track Fusion with Feedback” , Proc. of SPIE Conf. on Signal and Data Processing of Small Targets, Vol. 2759, pp. 342-360, April 1996.
- [4] R. Helmick, “IMM Estimator with Nearest-Neighbor Joint Probabilistic Data Association” , in *Multitarget-Multisensor Tracking: Applications and Advances*, Y. Bar-Shalom and W. D. Blair, Eds., 2000.
- [5] C. Jauffret, and Y. Bar-Shalom, “Track Formation with Bearing and Frequency Measurements in Clutter” *IEEE Transactions on Aerospace and Electronic Systems*, pp. 999-1010, November 1990.
- [6] S. Kay, *Fundamentals of Statistical Signal Processing, Vol. II–Detection Theory*, Prentice Hall, 1998.
- [7] T. Kirubarajan, and Y. Bar-Shalom, “Low Observable Target Motion Analysis Using Amplitude Information” , *IEEE Transactions on Aerospace and Electronic Systems*, 32(3), pp. 1367-1384, July 1996.
- [8] X. Li, Z-Q. Luo, K. M. Wong and E. Bosse, “An Interior Point Linear Programming Approach to Two-Scan Data Association” , *IEEE Trans. Aerospace and Electronic Systems*, 35(2), pp. 474-490, 1999.